PRODUCT RANGE SPECIFICATION

04TM_GEN-1160-04 – Genebre Metering Pillar Tap 15mm



PRODUCT IMAGE · Genebre 1160 04 Metering Pillar Tap

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Product range	**04TM_GEN-1160-04{PSS}**	**19 Nov 2026**

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/04tm_plu-029928-genebre-metering-pillartap-standard-cp-15mm#specifications

01 Product description and specification

Product description

Anti-vandal, chrome-plated brass pillar tap with push-button operation, timed automatic shut-off and a flow-limiting aerator for shared and public washrooms.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this product range.

Genebre 1160 04 standard anti-vandal metering pillar tap in chrome-plated brass. 15mm / G½″ BSP inlet; countertop mounting; push-button operation; automatic closure after 7–10 seconds at 3bar. 6L/min flow limiter. Inlet filter and fixing kit included.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Brand	Genebre	–	–
Material	Brass	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Finish	Chrome	–	–
Mounting Type	Countertop	–	–
Connection Thread	G½″ BSP (15mm)	–	–
Flow Rate	Up to 6L/min	–	–
Operating Pressure	Maximum 4bar (Local Listing)	–	–

03 Functional features

01 Timed Water Control
Automatic shut-off helps reduce water left running between handwashing uses.

02 Anti-Vandal Design
Vandal-resistant construction for frequent use in shared and public washrooms.

03 Controlled Flow
A 6L/min flow limiter and aerator provide a controlled water stream.

04 Chrome-Plated Brass
A brass body with a polished chrome finish complements shared washroom basins.

05 Fixing Kit Included
Supplied with a brass fixing nut and inlet filter for countertop installation.

04 Application information

Intended applications	General Handwashing, Public Restrooms

05 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

06 Frequently asked questions

How does the metering tap operate?
Press the button to start the water flow. The tap closes automatically after approximately 7–10 seconds at 3bar; actual timing varies with pressure.

Where can this tap be installed?
It is a countertop-mounted pillar tap for compatible handwashing basins. The inlet connection is 15mm / G½″ BSP.

What is included?
The tap includes a flow-limiting aerator, plastic inlet filter and fixing kit with a brass fixing nut.

What supply conditions should be checked?
The local Plumblink listing specifies a maximum pressure of 4bar and a maximum inlet temperature of 70°C. Confirm that the installation meets these limits.

E&OE. Specifications are subject to change without notice.