

PRODUCT RANGE SPECIFICATION

04TM_WAL-144S – Walcro 144S
Shower Metering Valve with Sleeve



PRODUCT IMAGE · Walcro 144S Shower Metering Valve with Sleeve

① Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE

Product range

DOCUMENT REFERENCE

04TM_WAL-144S{PSS}

DATA STATUS

Published catalogue data

GENERATED ON

6 Oct 2026

Detailed item specifications

Select an item code for its detailed specification sheet, including model dimensions, technical specifications and drawings. For a printed copy, scan the QR code or visit the product page and select the item.

https://basterfield.co.za/products/04tm_wal-144s-walcro-144s-shower-metering-valve-with-sleeve#specifications



01 Product description and specification

Product description

Walcro 144S 15mm built-in shower metering valve with sleeve and no-hold feature.
Operating pressure 30–600kPa, for public showers and secure ablutions.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Walcro 144S built-in shower metering valve, 15mm, with sleeve and no-hold feature.
Operating pressure: 30–600kPa. For public showers, communal ablutions and penal or correctional facilities.

02 Models and configurations

ITEM CODE

04TM_WAL-144S

03 Functional features

01 Built-In Installation with Sleeve

A concealed shower metering valve supplied with a sleeve for installation within the wall.

02 No-Hold Feature

Designed to prevent the shower control being held open for continuous flow.

03 30–600kPa Operating Range

A defined supply–pressure range for checking the proposed shower installation.

04 Public and Secure Shower Applications

Used in communal showers and secure ablutions, including penal and correctional facilities.

04 Application information

Intended applications

Change Rooms & Locker Rooms, Public Restrooms, Secure Ablutions

Industries	Government & Public Sector, Justice & Corrections
------------	---

05 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.