PRODUCT RANGE SPECIFICATION

04TM_WAL-144S – Walcro 144S Shower Metering Valve with Sleeve



PRODUCT IMAGE · Walcro 144S Shower Metering Valve with Sleeve

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Product range	**04TM_WAL-144S{PSS}**	**16 Nov 2026**

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/04tm_wal-144s-walcro-144s-shower-metering-valve-with-sleeve#specifications

01 Product description and specification

Product description

Walcro 144S 15mm built-in shower metering valve with sleeve and no-hold feature. Operating pressure 30–600kPa, for public showers and secure ablutions.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this product range.

Walcro 144S built-in shower metering valve, 15mm, with sleeve and no-hold feature. Operating pressure: 30–600kPa. For public showers, communal ablutions and penal or correctional facilities. Supplied as valve and sleeve; shower head and mixing components are separate.

02 Technical specifications

PARAMETER	VALUE	UNIT
Mounting Type	Built-in	–
Inlet Diameter	15	mm
Brand	Walcro	–
Operating Pressure	30–600kPa	–
Demand / Metered Valve	Metered Valve	–
Sleeve	Included	–

03 Functional features

01 **Built-In Installation with Sleeve**
A concealed shower metering valve supplied with a sleeve for installation within the wall.

02 **No-Hold Feature**
Designed to prevent the shower control being held open for continuous flow.

03 **30–600kPa Operating Range**
A defined supply-pressure range for checking the proposed shower installation.

04 **Public and Secure Shower Applications**
Used in communal showers and secure ablutions, including penal and correctional facilities.

04 Application information

Intended applications	Change Rooms & Locker Rooms, Public Restrooms, Secure Ablutions
Industries	Government & Public Sector, Prisons & Detention Facilities

05 Supply and support

Typical lead time	3 working days
Warranty	12 months

06 Frequently asked questions

What is the Walcro 144S?
It is a 15mm built-in shower metering valve supplied with a sleeve and a no-hold feature.

What operating pressure does it require?
The stated operating pressure range is 30–600kPa. Check the supply pressure at the installation against this range.

Where is it commonly used?
Typical applications include public showers, communal change-room showers and secure ablutions in penal or correctional facilities.

What is the no-hold feature for?
The no-hold feature is intended to prevent users holding the control open for continuous flow.

Is the 144S replacing the 155S?
Yes. The 144S is replacing the 155S in the Walcro range. For an existing installation, confirm the connections, mounting depth and service access before ordering.

Is this a complete shower assembly?
This item is the shower metering valve with its sleeve. Specify the other components required for the complete shower installation separately.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357