

PRODUCT RANGE SPECIFICATION

04TSH_WAL-CIRS-V2 – Walcro
CIRS-V2 Vandal Resistant Water
Saving Shower Head



PRODUCT IMAGE · Walcro CIRS-V2 Shower Head

① Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE

Product range

DOCUMENT REFERENCE

04TSH_WAL-CIRS-V2{PSS}

DATA STATUS

Published catalogue data

GENERATED ON

8 Oct 2026

Detailed item specifications

Select an item code for its detailed specification sheet, including model dimensions, technical specifications and drawings. For a printed copy, scan the QR code or visit the product page and select the item.

https://basterfield.co.za/products/04tsh_wal-cirs-v2-walcro-cirs-v2-vandal-resistant-water-saving-shower-head#specifications



01 Product description and specification

Product description

Walcro CIRS-V2 wall-mounted, vandal-resistant water-saving shower head with 15mm BSP female inlet, removable strainer and adjustable spray direction. Flow 6–8L/min depending on pressure; minimum pressure 100kPa.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Walcro CIRS-V2 wall-mounted water-saving shower head with 15mm (1/2in) BSP female inlet, vandal-resistant rotatable body, internal impeller and removable strainer. Flow 6–8L/min, pressure dependent; minimum supply pressure 100kPa (1bar).

02 Technical specifications

PARAMETER	VALUE	UNIT
Brand	Walcro	—
Inlet Diameter	15	mm
Mounting Type	Wall Mounted	—
Connection Thread	1/2in BSP Female	—
Flow Rate	6–8L/min (pressure dependent)	—
Minimum Operating Pressure	100kPa (1bar)	—

03 Models and configurations

ITEM CODE

04TSH_WAL-CIRS-V2

04 Functional features

01	Vandal-Resistant Wall Mounting The body locks in position with a grub screw, helping limit casual tampering in shared shower areas.
02	Water-Saving Shower Flow A flow range of 6–8L/min supports controlled water use in shared showers. Flow depends on supply pressure; minimum pressure is 100kPa (1bar).
03	Adjustable Jet Spray An internal impeller produces the jet spray. The rotatable body allows the spray to be aimed into the shower cubicle.
04	Removable Internal Strainer The internal strainer is removable, making it accessible for cleaning.
05	15mm BSP Female Connection The 15mm (1/2in) BSP female inlet provides a clearly specified connection for planning the shower pipework.

05 Application information

Intended applications	Change Rooms & Locker Rooms, Public Restrooms
Industries	General Manufacturing, Government & Public Sector

06 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.