

PRODUCT RANGE SPECIFICATION

04VF_WAL-103LUR – Walcro 20mm Exposed Urinal Flush Valve

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Product range	04VF_WAL-103LUR{PSS}	Published catalogue data	17 Sep 2026

01 Product description and specification

Product description	The Walcro 103LUR is an exposed, lever-operated flushing valve for a single bowl urinal. It has a 20 mm connection, chrome finish, flow control, a strainer and a no-hold feature. Its stated operating pressure range is 30–600 kPa. For the Basterfield B17744(T) top-entry bowl urinal, the recommended arrangement is one 04VF_WAL-103LUR valve together with one 04VFP-UR15TP 15 mm offset flush pipe per bowl. Selecting this valve for the bowl requires the offset pipe. Both accessories and the bowl are priced separately. Suitable applications include public and commercial washroom installations using exposed flushing controls. Check the available supply pressure and the complete connection layout before installation. This exposed valve is distinct from the concealed back-entry B17744(155UW) system recommended for B17744(B).
Short Form Specification	SPECIFICATION USE Use this description when specifying this product range. Walcro 103LUR exposed lever-operated urinal flushing valve, 20 mm connection, chrome finish, operating pressure 30–600 kPa, with flow control, strainer and no-hold feature. For B17744(T), specify one valve with one 04VFP-UR15TP offset flush pipe; separately priced.

02 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
04VF_WAL-103LUR	Walcro 103LUR exposed lever-operated urinal flushing valve, 20 mm connection, chrome finish, operating pressure 30–600 kPa, with flow control, strainer and no-hold feature. For B17744(T), specify one valve with one 04VFP-UR15TP offset flush pipe; separately priced.	Standard configuration

03 Functional features

01	Exposed lever operation Manual lever-operated flushing for a single bowl urinal.
02	20 mm connection Specified valve connection size is 20 mm.
03	30–600 kPa operating range Check the site supply against the stated operating pressure range.
04	Flow control and strainer Includes flow control, a strainer and a no-hold feature.

05 Use with the offset pipe

For B17744(T), specify one 04VFP-UR15TP pipe with each valve.

04 Application information

Intended applications	Public Restrooms
Industries	Colleges & Universities, Government & Public Sector, Hotels & Lodges, Restaurants & Cafés, Schools

05 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.