PRODUCT RANGE SPECIFICATION

04VF_WAL-104HT – Walcro 104HT Mobility-Impaired Top-Entry Flush Valve, 25 mm

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Product range	04VF_WAL-104HT{PSS}	Published catalogue data	30 Oct 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/04vf_wal-104ht-walcro-104ht-mobility-impaired-top-entry-flush-valve-25-mm#specifications

01 Product description and specification

Product description

Walcro 104HT exposed toilet flushing valve with a 25 mm inlet, extended lever for mobility-impaired users and a top-entry flush-pipe arrangement. The lever can be positioned for left-hand or right-hand operation.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this product range.

Walcro 104HT exposed mobility-impaired toilet flushing valve, 25 mm inlet, extended lever configurable for left-hand or right-hand operation and top-entry flush-pipe arrangement. For compatible top-entry WC pans; WC pan supplied separately.

02 Functional features

01 **Extended operating lever**
Extended lever intended for accessible and mobility-impaired toilet installations.

02 **Left- or right-hand operation**
The lever arrangement can be positioned to suit either operating side.

03 **Top-entry configuration**
Supplied for a compatible top-entry WC pan.

04 **25 mm inlet**
Specified with a 25 mm water inlet.

03 Application information

Intended applications	Public Restrooms
Industries	Government & Public Sector, Schools

04 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

05 Frequently asked questions

Who is the 104HT intended for?

It is intended for accessible and mobility-impaired toilet installations.

Can the lever be used on either side?

Yes. The extended lever can be positioned for left-hand or right-hand operation.

Which WC inlet does it suit?

The 104HT is the top-entry model and requires a compatible top-entry WC pan.

What inlet size does it use?

The specified water inlet size is 25 mm.

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357