

PRODUCT RANGE SPECIFICATION

04VF_WAL-106T – Walcro 106T Top-Entry Lever Flush Valve, 25 mm

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Product range	04VF_WAL-106T{PSS}	Published catalogue data	18 Sep 2026

01 Product description and specification

Product description	The Walcro 106T is an exposed, manually lever-operated flushing valve for a WC pan with a top-entry flush connection. The valve has a 25 mm BSP female water inlet, a chrome finish over DZR brass and a straight top-entry flush pipe. This valve is an optional alternative to the B17110(L380-DPB) cistern on compatible top-entry B17654, B17655, B17657 and B17659 models. Select the valve or the cistern to suit the installation. The WC pan is ordered separately. Applications include public restrooms and commercial, educational and industrial ablution facilities. The manufacturer specifies a maintained water pressure range of 30 to 600 kPa for the 106 series. Confirm the water supply, flow and pipe alignment for the selected pan before installation. The 106T uses the top-entry flush pipe arrangement. Back-entry WC pans require a suitable back-entry flushing system. The 25 mm size describes the water inlet connection; it is not an overall product dimension.
Short Form Specification	SPECIFICATION USE Use this description when specifying this product range. Walcro 106T exposed lever-operated toilet flushing valve for top-entry WC pans. Inlet: 25 mm BSP female. Material: DZR brass. Finish: chrome. Top-entry straight flush pipe. Manufacturer maintained pressure range: 30 to 600 kPa. Select as an optional alternative to a flushing cistern; WC pan supplied separately.

02 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
04VF_WAL-106T	Walcro 106T exposed lever-operated toilet flushing valve, top-entry type, with 25 mm BSP female inlet, chrome-finished DZR brass body and straight top-entry flush pipe. Optional alternative to a separate flushing cistern.	Standard configuration

03 Functional features

01	Top-entry flushing Straight flush pipe arrangement for a WC pan with a top-entry flushing connection.
02	Manual lever operation Exposed lever-operated valve for accessible operation and servicing.
03	25 mm BSP inlet Female water inlet connection; inlet size is separate from overall dimensions.

- 04 Chrome-finished DZR brass**
DZR brass valve body with chrome finish.
- 05 Optional cistern alternative**
Select the Walcro 106T or a suitable cistern to match the pan and installation.

04 Application information

Intended applications	Public Restrooms, Restrooms & Ablutions
Industries	Colleges & Universities, General Manufacturing, Government & Public Sector, Schools

05 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

Product drawings and images



PRODUCT IMAGE · Walcro 106T top-entry flushing valve and straight flush pipe.

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.