

PRODUCT RANGE SPECIFICATION

04VFP-UR15TP – UR15TP 15 mm Offset Flush Pipe

DOCUMENT SCOPE Product range	DOCUMENT REFERENCE 04VFP-UR15TP{PSS}	DATA STATUS Published catalogue data	GENERATED ON 17 Sep 2026
---------------------------------	---	---	-----------------------------

01 Product description and specification

Product description	04VFP-UR15TP is a 15 mm offset flush pipe for the recommended exposed flushing arrangement on the Basterfield B17744(T) top-entry bowl urinal. Specify one offset pipe together with one 04VF_WAL-103LUR Walcro 103LUR valve per bowl. If selecting the valve for B17744(T), include this pipe as well. The pipe, valve and bowl remain separate items with individual prices. The offset layout provides the connection between the selected valve and the top-entry bowl. Confirm the installed positions and connection alignment before fitting. The 15 mm designation is the pipe size, not its overall length. Typical applications include public and commercial restrooms, school and university washrooms and restaurant ablutions using the recommended exposed top-entry arrangement.
Short Form Specification	SPECIFICATION USE Use this description when specifying this product range. 04VFP-UR15TP, UR15TP 15 mm offset flush pipe. Recommended with one 04VF_WAL-103LUR valve per B17744(T) top-entry bowl urinal. Pipe size 15 mm; confirm installed alignment. Supplied and priced separately.

02 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
04VFP-UR15TP	04VFP-UR15TP, UR15TP 15 mm offset flush pipe. Recommended with one 04VF_WAL-103LUR valve per B17744(T) top-entry bowl urinal. Pipe size 15 mm; confirm installed alignment. Supplied and priced separately.	Standard configuration

03 Functional features

01	15 mm pipe size UR15TP offset flush pipe with a 15 mm size designation.
02	Offset layout Connecting pipework for the recommended exposed top-entry flushing arrangement.
03	One pipe per valve Use one pipe with each 04VF_WAL-103LUR valve on B17744(T).
04	Separately priced accessory Order the pipe, valve and bowl as separate items.

Intended applications	Public Restrooms
Industries	Colleges & Universities, Government & Public Sector, Hotels & Lodges, Restaurants & Cafés, Schools

05 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.