

MODEL SPECIFICATION

A03015(109-015) – Bucket, Grade 304 Stainless Steel, 0.9mm Thickness, 15L, with Swing Handle and Lid

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Model	A03015(109-015){PSS}	Published catalogue data	7 Oct 2026

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Capacity	15	L	—
Material Thickness	0.9	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.
Handle Type	Swing Handle	—	The carrying handle construction fitted to this milk-can product.
Drop-On Lid	Yes	—	—

02 Model and supply data

Parent product	A03015 – Straight-Sided Stainless Steel Buckets
Typical lead time	10–15 working days
Warranty	12 months

03 Specification notes

Configuration description	Straight-sided 15L bucket in Grade 304 stainless steel with 0.9mm material thickness and a swing handle. Supplied with a drop-on lid. For carrying liquids and process materials in food production, healthcare utility rooms and laboratory work areas. Select the material grade and cleaning procedure for the contents and workplace process. This 0.9mm configuration is available under advanced customisation.
---------------------------	---

Short Form Specification

SPECIFICATION USE

Use this description when specifying this model.

Basterfield A03015(109-015). Straight-sided 15L bucket in Grade 304 stainless steel with 0.9mm material thickness and a swing handle. Supplied with a drop-on lid.

Detailed specification	• Model: A03015(109-015) • Body: Straight-sided • Material: Grade 304 stainless steel • Material thickness: 0.9mm • Capacity: 15L • Handle: Swing handle • Drop-on lid: Included
------------------------	--

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.