PRODUCT RANGE SPECIFICATION

A03015 – Straight-Sided Stainless Steel Buckets



PRODUCT IMAGE · 20L Grade 316 bucket shown without lid. Select the required capacity, grade, thickness and lid arrangement.

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Product range	A03015{PSS}	17 Nov 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/a03015-straight-sided-heavy-duty-buckets#specifications

01 Product description and specification

Product description

Straight-sided stainless steel buckets with swing handles, in 10L, 12L, 15L, 20L and 30L capacities. Choose Grade 304 or Grade 316, with or without a drop-on lid. 1.2mm thickness is standard; 0.9mm is available under advanced customisation.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this product range.

Basterfield A03015 straight-sided stainless steel bucket with swing handle. Select 10L, 12L, 15L, 20L or 30L; Grade 304 or Grade 316; with drop-on lid or without lid. Standard material thickness: 1.2mm. Advanced material thickness: 0.9mm. Plain configuration codes include a drop-on lid; suffix -01 means without lid. Volume graduations are not specified for this standard range.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Handle Type	Swing Handle	–	The carrying handle construction fitted to this milk-can product.

03 Configuration options

Material	Stainless Steel Grade 304; Stainless Steel Grade 316
Capacity	10 L; 12 L; 15 L; 20 L; 30 L
Drop-On Lid	No; Yes

Options vary by model; not every combination is available. Use the product page to select a model.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

04 Functional features

01 Five Capacities
Choose 10L, 12L, 15L, 20L or 30L to suit the handling task.

02 Grade 304 or Grade 316
Both stainless steel grades are available at every listed capacity, with or without a lid.

03 1.2mm Standard Construction
1.2mm material thickness is standard. Enable advanced customisation to select 0.9mm.

04 Drop-On Lid Choice
Select a bucket with a drop-on lid or a bucket supplied without a lid.

05 Straight Sides and Swing Handle
A straight-sided body and swing handle provide a container for carrying liquids and process materials.

05 Application information

Intended applications	Healthcare Utility Rooms, Laboratory Work Areas, Liquid Storage & Handling, Material Handling
Industries	Clinical Laboratories, Food & Beverage Processing, Healthcare, Hospitals & Clinics, Research Laboratories

06 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

07 Frequently asked questions

Which capacities are available?
A03015 buckets are available in 10L, 12L, 15L, 20L and 30L capacities. Each capacity is available in Grade 304 or Grade 316 stainless steel, with or without a drop-on lid.

What is the standard material thickness?
The standard material thickness is 1.2mm. Enable advanced customisation in the configurator to reduce the thickness to 0.9mm.

Is a lid included?
The plain configuration code includes a drop-on lid. A code ending in -01 identifies a bucket supplied without a lid. For example, A03015(112-010) is the 10L Grade 304, 1.2mm bucket with lid; A03015(112-010)-01 is the same bucket without a lid.

How do the material codes work?
112 identifies Grade 304 stainless steel at 1.2mm, and 312 identifies Grade 316 at 1.2mm. Advanced 0.9mm options use 109 for Grade 304 and 309 for Grade 316. The final three digits inside the brackets give the capacity in litres.

Where can these buckets be used?
Typical applications include ingredient and liquid handling in food production, routine liquid and material handling in laboratory work areas, and cleaning or utility tasks in medical and healthcare facilities. Select the grade, capacity and cleaning method for the intended contents and local procedures.

Are volume graduations included?
Volume graduations are not specified for this standard range. Specify any graduation or measurement requirement when requesting a quotation.

How should I specify a bucket for my process?

Select the capacity, stainless steel grade and lid arrangement. 1.2mm is the standard thickness; 0.9mm is an advanced option. Include details of the contents, cleaning process and any additional requirements with the quotation request.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357