

MODEL SPECIFICATION

A03016(109-012-L) –
A03016(109-012-L) Stainless Steel
Tapered Bucket Grade 304 0.9mm
Thickness 12L and Drop-on Lid
Material Thickness: 0.9. Capacity:
12. Material: Stainless Steel Grade
304. Drop-On Lid: Yes.



PRODUCT IMAGE

DOCUMENT SCOPE
Model

DOCUMENT REFERENCE
A03016(109-012-L){PSS}

DATA STATUS
Published catalogue data

GENERATED ON
14 Sep 2026

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material Thickness	0.9	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.
Capacity	12	l	—
Material	Stainless Steel Grade 304	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Drop-On Lid	Yes	—	—

02 Model and supply data

Parent product	A03016 – Stainless Steel Tapered Bucket with Swing Handle
Typical lead time	10–15 working days
Warranty	12 months

03 Specification notes

Configuration description

Stainless steel tapered bucket with swing handle, reinforcing rim and optional drop-on lid. Compare published capacities, grades and material thicknesses.

Selected configuration: Material Thickness: 0.9 mm; Capacity: 12 L; Material: stainless steel Grade 304; Drop-On Lid: Yes.

Short Form Specification	SPECIFICATION USE Use this description when specifying this model. Basterfield A03016(109-012-L). Stainless steel tapered bucket with swing handle, reinforcing rim and optional drop-on lid. Compare published capacities, grades and material thicknesses. Selected configuration: Material Thickness: 0.9 mm; Capacity: 12 L; Material: stainless steel Grade 304; Drop-On Lid: Yes.
Detailed specification	• Model: A03016(109-012-L) • Material Thickness: 0.9 mm • Capacity: 12 L • Material: stainless steel Grade 304 • Drop-On Lid: Yes

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.