

MODEL SPECIFICATION

A08091(5000) – Flat Scoop in 1.2 mm Grade 304 Stainless Steel with a Nominal 5 kg Volumetric Capacity Based on Water Density. Grade 316 Is Available as an Alternative.



PRODUCT IMAGE

DOCUMENT SCOPE

Model

DOCUMENT REFERENCE

A08091(5000){PSS}

DATA STATUS

Published catalogue data

GENERATED ON

4 Oct 2026

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Capacity (kg)	5	kg	–
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	1.2	mm	The thickness of the material used for the item’s primary construction. The thickness of individual components may vary.

02 Model and supply data

Parent product	A08091 – Stainless Steel Flat Scoops
Typical lead time	5–10 working days
Warranty	12 months

03 Specification notes

Configuration description

The Basterfield A08091(5000) is a flat stainless steel scoop with a nominal 5 kg volumetric capacity. It is manufactured from 1.2 mm Grade 304 stainless steel as standard; Grade 316 is available as an alternative on request.

The stated capacity is based on the density of water. The mass held when scooping other materials will vary according to their bulk density.

The standard lead time is 5–10 working days. The published price excludes VAT.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this model.

Basterfield A08091(5000) flat scoop, nominal 5 kg volumetric capacity based on water density, manufactured from 1.2 mm Grade 304 stainless steel. Grade 316 is available as an alternative. Lead time: 5–10 working days.

Detailed specification

- Model: A08091(5000)
- Nominal volumetric capacity: 5 kg
- Capacity basis: Density of water
- Standard material: Grade 304 stainless steel
- Alternative material: Grade 316 stainless steel on request
- Material thickness: 1.2 mm
- Lead time: 5–10 working days
- Pricing: Excludes VAT

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.