PRODUCT RANGE SPECIFICATION

A20310 – Stainless Steel Product Storage Container with Clamp-On Lid and Gasket

PRODUCT IMAGE · 10L Grade 304, 1.2mm model shown. Other capacities and material configurations may differ.

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Product range	A20310{PSS}	Published catalogue data	30 Oct 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/a20310-stainless-steel-product-storage-container-with-clamp-on-lid-and-gasket#specifications

01 Product description and specification

Product description

Product storage container with clamp-on lid, toggle latches, food grade silicone gasket, barrel handles and a reinforcing bottom rim. Capacities from 10L to 50L. Standard 1.2mm Grade 304, with Grade 316 and 1.5mm options.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this product range.

Stainless steel product storage container with clamp-on lid, toggle latches, food grade silicone gasket, barrel handles and reinforcing bottom rim for strength and stability. Capacities: 10L, 20L, 30L, 40L and 50L. Standard: Grade 304 stainless steel, 1.2mm thickness. Options: Grade 316 and/or 1.5mm thickness.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Lid Type	Clamp-On Lid	–	A clamp-on lid secured with toggle latches and a food grade silicone gasket.
Toggle Latches	Yes	–	–
Gasket Material	Food Grade Silicone	–	–
Handle Type	Barrel Handles	–	Barrel handles provide handling points on the bucket.
Base Reinforcement	Reinforcing Bottom Rim	–	A reinforcing rim at the bottom adds strength and supports a stable base.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

03 Configuration options

Capacity	10 L; 20 L; 30 L; 40 L; 50 L

Options vary by model; not every combination is available. Use the product page to select a model.

04 Functional features

01 Clamp-On Lid and Silicone Gasket
Each container includes a clamp-on lid secured by toggle latches and a food grade silicone gasket at the lid closure.

02 Barrel Handles
Barrel handles provide handling points on the sides of the container.

03 Reinforcing Bottom Rim
The reinforcing rim at the bottom adds strength and supports a stable base.

04 Five Capacity Options
Select a 10L, 20L, 30L, 40L or 50L capacity to suit the required quantity of product.

05 Stainless Steel Construction Options
1.2mm Grade 304 stainless steel is standard. Grade 304 is also available in 1.5mm thickness, and Grade 316 in 1.2mm or 1.5mm thickness.

05 Application information

Intended applications	Liquid Storage & Handling, Material Handling, Processing & Production, Storage & Organisation
Industries	Dairy & Beverage Processing, Food & Beverage Processing, General Manufacturing

06 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

07 Frequently asked questions

Which capacities are available?
The available capacities are 10L, 20L, 30L, 40L and 50L.

What lid and seal are supplied?
Each container includes a clamp-on lid secured by toggle latches. A food grade silicone gasket seals the lid closure.

Which stainless steel grades and thicknesses can I specify?
1.2mm Grade 304 is standard. Grade 304 can also be specified in 1.5mm thickness, and Grade 316 in 1.2mm or 1.5mm thickness. All options are available across the five container capacities.

How is the container handled and supported?
Barrel handles provide handling points on the sides. A reinforcing bottom rim adds strength and supports a stable base.

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.