

PRODUCT RANGE SPECIFICATION

A25170 – Stainless Steel Conical Hopper with Tri-Clamp Ferrule



PRODUCT IMAGE

① Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE
Product range

DOCUMENT REFERENCE
A25170{PSS}

DATA STATUS
Published catalogue data

GENERATED ON
5 Oct 2026

01 Product description and specification

Product description

The A25170 conical hopper directs product towards a lower ferrule for connection to food processing and packaging equipment. It is manufactured from Grade 304 stainless steel with mirror-polished surfaces and a rolled top rim.

A tri-clamp connection secures the lower ferrule to compatible equipment. Select the required cone diameter and confirm the connection size against the receiving system.

For an upper cylindrical section providing additional volume above the cone, see the A25175 hopper range.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Basterfield A25170. Grade 304 stainless steel conical hopper; mirror-polished surfaces; rolled top rim; lower ferrule for tri-clamp connection. Cone diameter and connection size as specified.

02 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
A251700250	A251700250 Stainless Steel Conical Hopper with Tri-Clamp Ferrule Mounting 250mm Diameter	Cone Diameter (mm): 250 mm
	Cone Diameter (mm): 250.	
A251700350	A251700350 Stainless Steel Conical Hopper with Tri-Clamp Ferrule Mounting 350mm Diameter	Cone Diameter (mm): 350 mm
	Cone Diameter (mm): 350.	
A251700400	A251700400 Stainless Steel Conical Hopper with Tri-Clamp Ferrule Mounting 400mm Diameter	Cone Diameter (mm): 400 mm
	Cone Diameter (mm): 400.	

02 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
A251700600	A251700600 Stainless Steel Conical Hopper with Tri-Clamp Ferrule Mounting 600mm Diameter Cone Diameter (mm): 600.	Cone Diameter (mm): 600 mm

03 Application information

Intended applications	Material Handling
Industries	Food & Beverage Processing

04 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

Product drawings and images





PRODUCT IMAGE



PRODUCT IMAGE

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.