

PRODUCT RANGE SPECIFICATION

B08109 – Straight Stainless Steel Grab Rail

DOCUMENT SCOPE Product range	DOCUMENT REFERENCE B08109{PSS}	DATA STATUS Published catalogue data	GENERATED ON 18 Sep 2026
---------------------------------	-----------------------------------	---	-----------------------------

01 Product description and specification

Product description	The Basterfield B08109 is a straight general-purpose grab rail made from Grade 304 stainless steel. Its 32 mm diameter rail provides a handhold, with mounting plates at both ends for fixing to a suitable supporting wall. The range has two specified rail lengths: B08109(0500) at 500 mm and B08109(0750) at 750 mm. Choose the length to suit the planned handhold position and available installation space. Applications include handholds alongside toilets, baths or showers and within care-facility washrooms, subject to the project layout and installation requirements. Typical settings include hospitals, clinics, aged-care facilities, hotels, schools and public buildings. Confirm the supporting wall, fixing method, mounting position and required clearances before installation. Request mounting-plate dimensions, hole centres, wall clearance and load information where these are required for the project. Clean with products and methods suitable for Grade 304 stainless steel. Inspect the installed rail and its fixings as part of the facility maintenance routine. The product image is representative of the straight-rail design; rail length depends on the selected model.
Short Form Specification	SPECIFICATION USE Use this description when specifying this product range. Basterfield B08109 straight general-purpose grab rail, Grade 304 stainless steel, 32 mm rail diameter, with mounting plates at both ends. Specify B08109(0500), 500 mm rail length, or B08109(0750), 750 mm rail length. Confirm wall construction, fixings, mounting position and clearances for the installation.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Diameter	32	mm	Diameter of the tubular grab rail, not the mounting plates.
Mounting Type	Wall Mounted	—	—

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B08109(0500)	Straight general-purpose grab rail, Grade 304 stainless steel, 32 mm rail diameter, 500 mm rail length, with mounting plates at both ends.	Length: 500 mm Overall dimensions: 500 × – × – mm (L × W × H)
B08109(0750)	Straight general-purpose grab rail, Grade 304 stainless steel, 32 mm rail diameter, 750 mm rail length, with mounting plates at both ends.	Length: 750 mm Overall dimensions: 750 × – × – mm (L × W × H)

04 Functional features

01	Grade 304 stainless steel Rail manufactured from Grade 304 stainless steel.
02	32 mm rail diameter A 32 mm diameter tubular rail provides the handhold.
03	500 mm or 750 mm length Select B08109(0500) for 500 mm or B08109(0750) for 750 mm.
04	Mounting plates at both ends End mounting plates provide fixing points for attachment to a suitable supporting wall.
05	Straight handhold A straight central rail with returned ends, as shown in the representative product image.

05 Application information

Intended applications	Patient Care & Examination, Public Restrooms, Restrooms & Ablutions
Industries	Aged Care & Nursing Homes, Colleges & Universities, Government & Public Sector, Hospitals & Clinics, Hotels & Lodges, Schools

06 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

Product drawings and images

PRODUCT IMAGE · Representative straight grab rail; choose 500 mm or 750 mm rail length.

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.