

PRODUCT RANGE SPECIFICATION

B17110(L380-CPB) – Stainless Steel Low-Level Toilet Cistern

DOCUMENT SCOPE Product range	DOCUMENT REFERENCE B17110(L380-CPB){PSS}	DATA STATUS Published catalogue data	GENERATED ON 14 Sep 2026
---------------------------------	---	---	-----------------------------

01 Product description and specification

Product description	Grade 304 stainless steel low-level toilet cistern with lever-operated flushing, concealed wall fixings and a 50 mm flush outlet. Constructed from Grade 304 stainless steel, this cistern is engineered for durability, corrosion resistance, and ease of maintenance. The unit operates via a lever flush mechanism and features a fully welded, crevice-free design, ensuring structural integrity and high hygiene standards. The stainless steel casing provides additional protection against impact and tampering, making it suitable for demanding installations. Designed for secure wall mounting, the cistern includes concealed fixings to reduce the risk of vandalism. An anti-vandal inspection panel allows controlled access for maintenance while safeguarding internal components. The cistern is assembled with inlet and outlet valves, both of which are adjustable to allow precise flushing volume control. The inlet valve can be configured for either left-hand or right-hand operation, accommodating different plumbing layouts. The outlet is a 50 mm flush outlet, suitable for connection to compatible toilets or urinals. Specifications: • Installation: Wall-mounted, low-level cistern. • Flush Operation: Lever flush. • Material: Grade 304 stainless steel. • Construction: Fully welded, seamless design for hygiene and durability. • Fixing: Concealed wall fixings for security. • Inspection Access: Anti-vandal inspection panel. • Valves: Adjustable inlet and outlet valves. • Inlet Position: Configurable as left-hand or right-hand. • Outlet Size: 50 mm flush outlet for connection to WC or urinal.
---------------------	--

Short Form Specification	SPECIFICATION USE Use this description when specifying this product range. Basterfield B17110(L380-CPB) wall-mounted low-level cistern, Grade 304 stainless steel with lever-operated flushing and 50 mm flush outlet. Inlet configuration and flushing volume as specified.
--------------------------	--

02 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B17110(L380-CPB)	Cistern Universal Side Entry & Bung	Standard configuration

03 Application information

Intended applications	Public Restrooms
Industries	Government & Public Sector

04 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

Product drawings and images



VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.