

MODEL SPECIFICATION

B17642(S) – Floor-Mounted WC Pan in 1.2 mm Grade 304 Stainless Steel, S-Trap with Vertical Outlet, Brushed Satin Finish, 102 mm OD Waste Outlet and Back-Entry Flush Inlet. Toilet Seat and Flushing System Specified Separately.



PRODUCT IMAGE

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Model	B17642(S){PSS}	Published catalogue data	4 Oct 2026

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Trap Type	S-Trap	–	–
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	1.2	mm	The thickness of the material used for the item’s primary construction. The thickness of individual components may vary.

02 Model and supply data

Parent product	B17642 – Stainless Steel Pedestal Toilets
Typical lead time	10–15 working days
Warranty	12 months

Configuration description	Basterfield B17642(S) is a floor-mounted pedestal WC pan with a S-Trap and a vertical waste outlet for public and institutional washrooms. The pan is manufactured from 1.2 mm Grade 304 stainless steel with a brushed satin finish and radiused edges. The waste outlet has an outside diameter of 102 mm for connection to 110 mm PVC soil pipe. Base flanges with pre-drilled 6 mm holes provide the floor-fixing points. An integral flushing rim and back-entry flush-pipe inlet. Choose one separately priced flushing system: B17110(L380-CPB) 9 L stainless steel cistern with PVC flush pipe and rubber bung; 04VF_WAL-106B Walcro 106B exposed lever-operated back-entry valve; or 04VF_WAL-103LC Walcro 103LC concealed back-entry valve with VR push button and concealed pipes. Standard seat-mounting holes are provided. Toilet seats and flushing systems are available on request and must be specified separately. Manufactured in South Africa.
Short Form Specification	SPECIFICATION USE Use this description when specifying this model. Basterfield B17642(S) floor-mounted pedestal WC pan; 1.2 mm Grade 304 stainless steel with brushed satin finish; S-Trap with vertical 102 mm outside-diameter outlet for 110 mm PVC soil pipe; integral flushing rim and rear-entry flush-pipe inlet; base flanges with pre-drilled 6 mm fixing holes; standard seat-mounting holes. Toilet seat specified separately. Choose one separately priced flushing system: B17110(L380-CPB) 9 L stainless steel cistern with PVC flush pipe and rubber bung; 04VF_WAL-106B Walcro 106B exposed lever-operated back-entry valve; or 04VF_WAL-103LC Walcro 103LC concealed back-entry valve with VR push button and concealed pipes.
Detailed specification	• Manufacturer: Basterfield • Model: B17642(S) • Product type: Floor-mounted pedestal WC pan • Material: Grade 304 stainless steel • Material thickness: 1.2 mm • Finish: Brushed satin • Trap type: S-Trap • Waste outlet direction: Vertical • Waste outlet outside diameter: 102 mm • Soil-pipe connection: 110 mm PVC soil pipe • Flush arrangement: Integral flushing rim and rear/back-entry flush-pipe inlet • Flush inlet: Accommodates a rubber sealing bung • Optional flushing systems: B17110(L380-CPB), 04VF_WAL-106B or 04VF_WAL-103LC; select one and price separately • Mounting: Base flanges with pre-drilled 6 mm floor-fixing holes • Toilet seat: Standard mounting holes provided; seat specified separately • Origin: Manufactured in South Africa

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.