
MODEL SPECIFICATION

B17652(PE) – Toilet Prison External Flanges 250mm Pipe Length



PRODUCT IMAGE

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	B17652(PE){PSS}	14 Nov 2026

01 Model specification

Shrouded Prison Toilet Pan, Grade 304 Stainless Steel, 1.2mm Material Thickness, 550mm (L) Projection × 360mm (W) × 433mm (H), with External Floor and Wall Mounting Flanges, Integral P-Trap, 110mm Waste Outlet and Rear-Entry Flush Inlet, with 250mm Inlet and Outlet Pipe Extensions

02 Technical specifications

PARAMETER	VALUE	UNIT
Extended Pipes	Yes	–

03 Model and supply data

Parent product	B17652 — Stainless Steel Prison Toilet with External Mounting Flanges
Typical lead time	10–15 working days
Warranty	12 months

04 Specification notes

Configuration description

The B17652(PE) is the B17652 shrouded Grade 304 stainless steel WC pan with external mounting flanges and 250 mm inlet and outlet pipe extensions.

The 1.2 mm stainless steel pan incorporates an integral P-trap, a 110 mm waste outlet and a rear-entry flush inlet. Standard pan dimensions are 550 mm projection × 360 mm width × 433 mm height. A compatible concealed flushing arrangement is installed behind the wall. Seat mounting holes are not provided as standard.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this model.

Basterfield B17652(PE) shrouded prison WC pan; Grade 304 stainless steel, 1.2 mm; standard pan dimensions 550 × 360 × 433 mm (projection × width × height); external mounting flanges; integral P-trap; 110 mm waste outlet; rear-entry flush inlet; 250 mm inlet and outlet extensions.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

Detailed specification

- Model: B17652(PE)
- Product type: Shrouded prison WC pan
- Material: Grade 304 stainless steel
- Material thickness: 1.2 mm
- Standard pan dimensions: 550 mm projection × 360 mm width × 433 mm height
- Mounting: External floor and wall flanges
- Trap: Integral P-trap
- Waste outlet: 110 mm
- Flush inlet: Rear entry
- Flushing arrangement: Compatible concealed flush valve or concealed cistern behind the wall
- Extended pipes: 250 mm inlet and outlet extensions
- Seat mounting holes: Not provided as standard

05 Frequently asked questions

What is the difference between the two configurations?

B17652(P) has standard pipes. B17652(PE) has 250 mm inlet and outlet pipe extensions for routing through the wall. Both use external mounting flanges and an integral P-trap.

Which flushing arrangement does this pan use?

The pan has a rear-entry flush inlet and can be used with a compatible concealed flush valve or concealed cistern installed behind the wall. Specify the required flushing arrangement with the installation.

Does the pan have seat mounting holes?

No seat mounting holes are provided as standard.

Is this the model with internal mounting flanges?

No. B17652 uses external mounting flanges. B17653 is the separate range with internal mounting flanges.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357