MODEL SPECIFICATION

B17654(PB-H) – Toilet Wall-Mounted P-Trap with Seat Holes

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	B17654(PB-H){PSS}	14 Nov 2026

01 Model specification

Wall-Mounted WC Pan, Grade 304 Stainless Steel, 1.2mm Material Thickness, Ø62mm Back-Entry Flush Inlet, 102mm OD Waste Outlet for 110mm PVC Soil Pipe, with P-Trap, Wall Plate with Four Ø12mm Fixing Holes, Pre-Punched Toilet Seat Mounting Holes, Basterfield B17654(PB-H)

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Seat Mounting Holes	Pre-Punched	—	Whether the WC pan has pre-punched toilet seat mounting holes.

03 Model and supply data

Parent product	B17654(PB) — Wall-Mounted Stainless Steel Toilet with P-Trap
Typical lead time	10–15 working days
Warranty	12 months

04 Specification notes

Configuration description

The B17654(PB-H) is the wall-mounted Grade 304 stainless steel P-trap WC pan with holes pre-punched for toilet seat mounting.

Both configurations use 1.2 mm stainless steel, a tapered 62 mm back-entry flush inlet and a 102 mm OD waste outlet for a 110 mm PVC soil pipe. The pan slides onto its stainless steel wall plate and is secured from the sides. The wall plate has four 12 mm fixing holes. Specify a compatible concealed cistern or flush valve for the installation.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this model.

Basterfield B17654(PB-H) wall-mounted WC pan; Grade 304 stainless steel, 1.2 mm; P-trap; tapered 62 mm back-entry flush inlet; 102 mm OD waste outlet for 110 mm PVC soil pipe; wall plate with four 12 mm fixing holes; brushed satin finish; pre-punched toilet seat mounting holes.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

Detailed specification

- Model: B17654(PB-H)
- Product type: Wall-mounted WC pan
- Material: Grade 304 stainless steel
- Material thickness: 1.2 mm
- Finish: Brushed satin
- Trap: P-trap
- Flush inlet: Back entry, tapered, 62 mm diameter
- Waste outlet: 102 mm OD for 110 mm PVC soil pipe
- Mounting: Stainless steel wall plate; pan secured from the sides
- Wall-plate fixing holes: Four, 12 mm diameter
- Seat mounting holes: Pre-Punched
- Flushing system: Compatible concealed cistern or flush valve

05 Frequently asked questions

Which seat mounting hole option should I select?

Select Not Pre-Punched for the standard B17654(PB) pan, or Pre-Punched for B17654(PB-H). The latter is the same toilet with holes pre-punched for mounting a toilet seat.

How is the pan mounted?

The stainless steel wall plate has four pre-punched 12 mm fixing holes. The pan slides onto the plate and is secured from the sides. These wall-plate fixing holes are separate from the selectable toilet seat mounting holes.

What are the flush inlet and waste outlet sizes?

Both options have a tapered 62 mm diameter back-entry flush inlet and a 102 mm outside-diameter waste outlet for connection to a 110 mm PVC soil pipe.

Which flushing arrangement does this pan use?

The back-entry inlet is intended for a compatible concealed cistern or concealed flush valve. Specify the required arrangement for the installation.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357