


MODEL SPECIFICATION

B17654(PT) – Stainless Steel Toilet Wall Mounted with P-Trap, Top-Entry Flush Inlet and No Toilet Mounting Holes. Excludes toilet seat and flush valve unless otherwise specified.



PRODUCT IMAGE · Top-entry pan shown. Optional toilet mounting holes are specified separately; seat and flushing system excluded.

DOCUMENT SCOPE Model	DOCUMENT REFERENCE B17654(PT){PSS}	DATA STATUS Published catalogue data	GENERATED ON 18 Sep 2026
-------------------------	---------------------------------------	---	-----------------------------

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Trap Type	P-Trap	–	–
Flushing Inlet Orientation	Top Entry	–	–
Toilet Mounting Holes	No holes	–	Optional standard toilet mounting holes. No holes as standard; -H identifies the holes variant.

02 Model and supply data

Parent product	B17654(PT) – Wall-Mounted Stainless Steel Toilet with Top Entry
Typical lead time	10–15 working days
Warranty	12 months

03 Specification notes

Configuration description

Stainless Steel Toilet Wall Mounted with P-Trap, Top-Entry Flush Inlet and No Toilet Mounting Holes. Excludes toilet seat and flush valve unless otherwise specified.

The B17654 top-entry WC pan is a wall-mounted stainless steel toilet with a P-trap and a top-entry flush inlet. It is intended for public, commercial, educational and institutional ablution facilities.

Toilet mounting holes are omitted by default. Select the optional standard toilet mounting holes when required; the selected item code gains the -H suffix. For the P-trap, top-entry version, B17654(PT) has no toilet mounting holes and B17654(PT-H) has standard toilet mounting holes.

Excludes toilet seat and flush valve unless otherwise specified. A flushing system is selected and priced separately. Compatible top-entry models offer the B17110(L380-DPB) 9 L stainless steel cistern or, as an alternative, the Walcro 106T exposed lever-operated flushing valve with a 25 mm inlet. Select the flushing arrangement for the available water supply and installation layout.

Coordinate the wall support, waste outlet, flushing connection and selected seat with the site layout. Specify the mounting-hole option when ordering.

Short Form Specification	SPECIFICATION USE Use this description when specifying this model. B17654(PT). Stainless Steel Toilet Wall Mounted with P-Trap, Top-Entry Flush Inlet and No Toilet Mounting Holes. Excludes toilet seat and flush valve unless otherwise specified.
Detailed specification	Model: B17654(PT) Material: Stainless steel Mounting: Wall mounted Trap type: P-Trap Flushing inlet: Top Entry Toilet mounting holes: No holes (standard) Excluded: Toilet seat and flush valve unless otherwise specified Optional flushing: B17110(L380-DPB) cistern or Walcro 106T valve

VERIFICATION REQUIRED

Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.