PRODUCT RANGE SPECIFICATION

B17656 – Close Coupled Shrouded Stainless Steel Toilets



PRODUCT IMAGE · B17656(CTP) P-Trap model shown. Trap outlet and toilet seat mounting holes vary by selected model.

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Product range	B17656{PSS}	Published catalogue data	3 Nov 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/b17656-close-coupled-toilet#specifications

01 Product description and specification

Product description

Grade 304 close-coupled shrouded stainless steel toilets with top-entry flushing, cistern and internal mechanism. Select P-Trap or S-Trap and the toilet seat mounting hole option.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this product range.

Shall be Basterfield B17656 Close Coupled Shrouded Stainless Steel Toilet, Grade 304 Stainless Steel with Satin Brushed Finish, Complete with Close-Coupled Stainless Steel Cistern and Internal Flushing Mechanism. Overall Dimensions: 650mm (L) × 360mm (W) × 800mm (H); Seat Height: 410mm. Top-Entry Flushing, Integral Flushing Rim, Front-Mounted Flush Lever and Side Maintenance Access Panels. Select P-Trap or S-Trap and the Toilet Seat Mounting Hole Option for the Required Model.

02 Configuration options

Trap Type	P-Trap; S-Trap
Toilet Seat Mounting Holes	Not Pre-Punched; Pre-Punched

Options vary by model; not every combination is available. Use the product page to select a model.

03 Functional features

01 **Grade 304 stainless steel**
The toilet suite is manufactured from Grade 304 stainless steel with a satin brushed finish.

02 **Complete close-coupled cistern**
Supplied complete with a close-coupled stainless steel cistern and internal flushing mechanism.

03 **P-Trap or S-Trap Outlet**
Select the integral P-Trap or S-Trap outlet specified for the required model.

04 **Integral flushing rim**
An integral flushing rim provides wash-down around the toilet bowl.

05 **Front-mounted flush lever**
The flushing mechanism is operated by a front-mounted lever / handle.

06 **Side maintenance access**
Side access panels provide access to the plumbing and internal flushing mechanism.

07 **Toilet Seat Mounting Hole Options**
The -H models include pre-punched toilet seat mounting holes. B17656(CTP) is supplied without pre-punched seat mounting holes.

04 Application information

Intended applications	Public Restrooms, Restrooms & Ablutions, Secure Ablutions
Industries	General Manufacturing, Government & Public Sector, Hospitals & Clinics, Prisons & Detention Facilities, Schools

05 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

06 Frequently asked questions

What is included with the B17656 close-coupled toilet?
It is supplied complete with a close-coupled stainless steel cistern and internal flushing mechanism.

What are the overall dimensions and seat height?
Overall dimensions are 650 mm long × 360 mm wide × 800 mm high. The seat height is 410 mm.

Which waste outlet and flush entry does it use?
All models use top-entry flushing. B17656(CTP) and B17656(CTP-H) have an integral P-Trap outlet; B17656(CTS-H) has an integral S-Trap outlet.

How is the toilet flushed?
A front-mounted flush lever / handle operates the internal flushing mechanism, and the integral flushing rim provides bowl wash-down.

How is the flushing mechanism accessed for maintenance?
Side access panels provide maintenance access to the plumbing and flushing mechanism.

What material and finish are used?
The suite is manufactured from Grade 304 stainless steel with a satin brushed finish.

Where are the B17656 toilets manufactured?
It is designed and manufactured in South Africa.

What does the -H suffix mean?
The -H suffix means pre-punched toilet seat mounting holes. Choose B17656(CTP-H) for P-Trap with holes or B17656(CTS-H) for S-Trap with holes. B17656(CTP) is the P-Trap model without pre-punched seat mounting holes.

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357