
MODEL SPECIFICATION

B17657(SB) – Toilet Accessible Floor-Mounted S-Trap Back-Entry



PRODUCT IMAGE

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	B17657(SB){PSS}	14 Nov 2026

01 Model specification

Accessible WC Pan, Grade 304 Stainless Steel, with S-Trap, Back-Entry Flush Inlet, Satin Finish, Floor and Back-to-Wall Mounting, Secure Internal Fixings and Side Access Panels, Basterfield B17657(SB)

02 Technical specifications

PARAMETER	VALUE	UNIT
Trap Type	S-Trap	–
Flushing Inlet Orientation	Back Entry	–

03 Model and supply data

Parent product	B17657 — Accessible Stainless Steel Floor-Mounted Toilet
Typical lead time	10–15 working days
Warranty	12 months

04 Specification notes

Configuration description

The B17657(SB) is the B17657 Grade 304 stainless steel WC pan with a S-Trap outlet and back entry flush inlet.

The satin-finished pan is intended for floor and back-to-wall installation using secure internal fixings. Side access panels provide access to the concealed plumbing. Match the selected trap and flush inlet to the drainage and flushing arrangement for the installation.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this model.

Basterfield B17657(SB) WC pan for accessible washroom layouts; heavy-gauge Grade 304 stainless steel, satin finish; S-Trap outlet; back entry flush inlet; floor and back-to-wall mounting with secure internal fixings; side plumbing access panels.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

Detailed specification

- Model: B17657(SB)
- Product type: WC pan for accessible washroom layouts
- Material: Heavy-gauge Grade 304 stainless steel
- Finish: Satin
- Trap type: S-Trap
- Flushing inlet: Back Entry
- Mounting: Floor and back to wall with secure internal fixings
- Maintenance access: Side panels for concealed plumbing

05 Frequently asked questions

Which choices identify the required model?

Select Trap Type and Flushing Inlet Orientation. The published range combines P-trap or S-trap with top-entry or back-entry flushing.

How do top-entry and back-entry flushing differ?

Top-entry models suit exposed cisterns or flush valves. Back-entry models suit concealed flushing arrangements. Match the inlet to the planned installation.

How is the concealed plumbing accessed?

Side access panels provide access to the concealed plumbing. The pan uses secure internal wall and floor fixings.

What are the dimensions of B17657(PB)?

B17657(PB) has overall dimensions of 800 mm projection × 360 mm width × 410 mm height. Check the selected model details when specifying the installation.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357