

MODEL SPECIFICATION

B17659(PT-H) – Shrouded Disabled WC Pan Wall Mounted with P-Trap, Top-Entry Flush Inlet and Standard Toilet Mounting Holes. Excludes toilet seat and flush valve unless otherwise specified.



PRODUCT IMAGE · Top-entry pan shown. Optional toilet mounting holes are specified separately; seat and flushing system excluded.

DOCUMENT SCOPE Model	DOCUMENT REFERENCE B17659(PT-H){PSS}	DATA STATUS Published catalogue data	GENERATED ON 18 Sep 2026
-------------------------	---	---	-----------------------------

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Trap Type	P-Trap	—	—
Flushing Inlet Orientation	Top Entry	—	—
Toilet Mounting Holes	Standard toilet mounting holes	—	Optional standard toilet mounting holes. No holes as standard; -H identifies the holes variant.

02 Model and supply data

Parent product	B17659(PT) – Accessible Stainless Steel WC Pan with P-Trap and Top Entry
Typical lead time	10–15 working days
Warranty	12 months

03 Specification notes

Configuration description	Shrouded Disabled WC Pan Wall Mounted with P-Trap, Top-Entry Flush Inlet and Standard Toilet Mounting Holes. Excludes toilet seat and flush valve unless otherwise specified. The B17659(PT) is a shrouded wall-mounted Grade 304 stainless steel WC pan with a P-trap and top-entry flush inlet. It is intended for accessible washroom layouts and includes a wall-mounting bracket. B17659(PT) is supplied without toilet mounting holes as standard. Select the optional standard toilet mounting holes to choose B17659(PT-H). Excludes toilet seat and flush valve unless otherwise specified. The B17110(L380-DPB) 9 L stainless steel cistern and Walcro 106T exposed lever-operated top-entry valve are optional, separately priced flushing alternatives. Select one flushing arrangement to match the water supply and installation. Coordinate wall support, waste outlet and flushing connections with the site layout. Plan the accessible installation as a complete washroom layout, including mounting height and clearances.
---------------------------	---

Short Form Specification	SPECIFICATION USE Use this description when specifying this model. B17659(PT-H). Shrouded Disabled WC Pan Wall Mounted with P-Trap, Top-Entry Flush Inlet and Standard Toilet Mounting Holes. Excludes toilet seat and flush valve unless otherwise specified.
Detailed specification	Model: B17659(PT-H) Material: Stainless Steel Grade 304 Mounting: Wall mounted Trap type: P-Trap Flushing inlet: Top Entry Toilet mounting holes: Standard toilet mounting holes Excluded: Toilet seat and flush valve unless otherwise specified Optional flushing: B17110(L380-DPB) cistern or Walcro 106T valve

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.