

PRODUCT RANGE SPECIFICATION

B17659(SB) – Accessible Stainless Steel WC Pan with S-Trap and Back Entry

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Product range	B17659(SB){PSS}	Published catalogue data	18 Sep 2026

01 Product description and specification

Product description	The B17659(SB) is a shrouded wall-mounted Grade 304 stainless steel WC pan with a S-trap and back-entry flush inlet. It is intended for accessible washroom layouts and includes a wall-mounting bracket. This B17659(SB) model is supplied without toilet mounting holes. Excludes toilet seat and flush valve unless otherwise specified. Use a flushing system suited to the back-entry inlet and installation layout. Top-entry flushing accessories are not offered on this model. Coordinate wall support, waste outlet and flushing connections with the site layout. Plan the accessible installation as a complete washroom layout, including mounting height and clearances.
Short Form Specification	SPECIFICATION USE Use this description when specifying this product range. Basterfield B17659(SB). Shrouded wall-mounted Grade 304 stainless steel WC pan; S-trap; back-entry flush inlet; wall-mounting bracket included; no toilet mounting holes as standard. Excludes toilet seat and flush valve unless otherwise specified.

02 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B17659(SB)	B17659(SB) Wall Mounted Disabled WC Pan S-Trap Back-Entry Trap Type: S-Trap. Flushing Inlet Orientation: Back Entry.	Standard configuration

03 Functional features


01	Grade 304 stainless steel Shrouded stainless steel WC pan for accessible washroom layouts.
02	Wall-mounted installation Wall-mounting bracket included.
03	S-trap and back-entry inlet Fixed S-trap and back-entry flushing connection for this model.
04	Seat and flush valve excluded Excludes toilet seat and flush valve unless otherwise specified.

Intended applications	Public Restrooms, Restrooms & Ablutions
Industries	Colleges & Universities, General Manufacturing, Government & Public Sector, Hospitals & Clinics, Schools

05 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

Product drawings and images



PRODUCT IMAGE · Back-entry pan illustration. Refer to the selected model specifications for the S-trap outlet arrangement.

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.