

MODEL SPECIFICATION

B17685LST – Basterfield B17685LST maximum-security combined toilet and wash hand basin, Grade 304 stainless steel. Left WC pan; concealed toilet paper holder included; security wall sleeve included.



PRODUCT IMAGE

DOCUMENT SCOPE
Model

DOCUMENT REFERENCE
B17685LST{PSS}

DATA STATUS
Published catalogue data

GENERATED ON
14 Sep 2026

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
WC Pan Orientation	Left	–	Select the WC pan position relative to the wash hand basin: left, centre or right. Confirm the handing against the project layout before ordering.
Toilet Paper Holder	Yes	–	Optional extra. Select Yes for a unit with an integral concealed toilet paper holder, or No for a unit without it. B17685(C) and B17685(R) exclude the holder.
Security Wall Sleeve	Yes	–	Choose whether a galvanised mild steel security wall sleeve with integral anti-escape bars is included. The sleeve is built into the wall and the unit is secured from behind with threaded rods.

02 Model and supply data

Parent product	B17685 – Maximum Security Combined Toilet and Wash Hand Basin
Typical lead time	10–15 working days
Warranty	12 months

Configuration description	The Basterfield B17685LST combines a left-position WC pan and wash hand basin in a one-piece Grade 304 stainless steel unit for prisons, holding cells and detention facilities. The pan position is relative to the basin and should be confirmed against the project layout. The shrouded WC pan encloses the P-trap and has an integral flushing rim designed to prevent contraband storage. The basin has a 40 mm waste outlet, with a 150 mm high rear splashback. This configuration includes an integral concealed toilet paper holder. It also includes a galvanised mild steel security wall sleeve with integral anti-escape bars. The sleeve is built into the wall and the unit is secured from behind with threaded rods. Security tapware is optional and must be specified in the quotation. The described arrangement uses a concealed flush valve with splashback-mounted push-button operation and a metered spout for handwashing and drinking-fountain use. Confirm mounting access, pan handing and plumbing connections for the selected installation.
Short Form Specification	SPECIFICATION USE Use this description when specifying this model. Basterfield B17685LST combined WC pan and wash hand basin for secure ablutions. One-piece Grade 304 stainless steel construction; left WC pan relative to the basin; shrouded P-trap; integral flushing rim; 40 mm basin waste outlet; 150 mm high rear splashback. Concealed toilet paper holder: included. Security wall sleeve: included. Sleeve in galvanised mild steel with integral anti-escape bars. Rear threaded-rod mounting. Security tapware optional, specified separately.
Detailed specification	• Model: B17685LST • Application: secure ablutions in prisons, holding cells and detention facilities • Unit construction: one-piece Grade 304 stainless steel • WC pan position: Left, relative to the wash hand basin • WC pan: shrouded, enclosing the P-trap • Flushing rim: integral, designed to prevent contraband storage • Basin waste outlet: 40 mm • Rear splashback height: 150 mm • Integral concealed toilet paper holder: Included • Security wall sleeve: Included • Sleeve construction: galvanised mild steel with integral anti-escape bars • Sleeve installation: built into the wall; unit secured to sleeve from behind with threaded rods • Security tapware: optional; specify separately in the quotation • Installation: confirm pan handing, rear mounting access and plumbing connections

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.