MODEL SPECIFICATION

# B17710(1065R) – Floor Mounted Curved Back Urinal 1065 RH



PRODUCT IMAGE

| DOCUMENT SCOPE | DOCUMENT REFERENCE | GENERATED ON |
|---|---|---|
| Model | B17710(1065R){PSS} | 15 Nov 2026 |

## 01 Model specification

Floor Mounted Curved Back Urinal Type FV to B17710(PSS) 1065MM Right Hand Outlet

## 02 Technical specifications

| PARAMETER | VALUE | UNIT | TECHNICAL NOTE |
|---|---|---|---|
| Waste Outlet Orientation | Right Hand | – | – |
| Length | 1065 | mm | The length of the item typically as measured from left to right. |

## 03 Model and supply data

| | |
|---|---|
| Parent product | B17710 — Stainless Steel Curved Back Urinal |
| Typical lead time | 10–15 working days |
| Warranty | 12 months |


121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

## 04 Specification notes

**Configuration description**

The Basterfield B17710 is the flush-valve version of the stainless steel curved-back trough urinal. Water is supplied through a flush valve to the concealed sparge pipe, which distributes flushing water across the urinal. The chosen flush valve and control arrangement determine how a flush is initiated.

B17710 does not incorporate the drip-fed tipping tray fitted to B17720. For built-in mechanical automatic flushing, choose B17720: its tipping tray slowly fills through a drip cock, periodically tips over to release the collected water and flush the urinal, then returns to fill again. B17720 uses this mechanical filling cycle rather than infrared detection or electronic control.

B17710 has welded Grade 304 stainless steel construction, a satin finish, a curved back, a sloped drip ledge and a sound-deadened back panel. A concealed sparge pipe is supplied from the top inlet. Select the required length and a centre, left-hand or right-hand 70 mm waste outlet to suit the plumbing layout. Confirm the flush valve, inlet connection and end details when specifying the installation.

Selected configuration: Waste Outlet Orientation: Right-Hand; Length: 1065 mm.

**Short Form Specification**

**SPECIFICATION USE**
Use this description when specifying this model.

Basterfield B17710(1065R) curved-back trough urinal, flush-valve type; welded Grade 304 stainless steel with satin finish; concealed sparge pipe and top water inlet; sound-deadened back panel; 70 mm waste outlet in the selected centre, left-hand or right-hand position; length as selected. Flushing actuation is determined by the specified flush valve and control arrangement. No integral drip-fed tipping tray; specify B17720 for built-in mechanical auto-flush. Selected configuration: Waste Outlet Orientation: Right-Hand; Length: 1065 mm.

**Detailed specification**

- Model: B17710(1065R)
- Waste Outlet Orientation: Right-Hand
- Length: 1065 mm
- Flushing arrangement: Flush-valve type with concealed sparge pipe
- Flush activation: Determined by the specified flush valve and control
- Integral mechanical tipping tray: Not fitted; see B17720 for this arrangement

## 05 Frequently asked questions

**What is the difference between B17710 and B17720?**

B17710 is the flush-valve version of the curved-back urinal. B17720 incorporates a mechanical automatic-flush tipping tray: water enters through a drip cock, the tray fills and periodically tips over to flush, then refills. The B17720 mechanism is not infrared or electronically controlled.

**How is B17710 flushed?**

A flush valve supplies water to the concealed sparge pipe. The selected valve and control arrangement determine how the flush is initiated. Specify that arrangement with your quotation; B17710 does not contain the built-in tipping tray used by B17720.

**Does B17710 identify an infrared or electronic flush system?**

B17710 identifies the flush-valve urinal model. The activation method depends on the valve and control specified for the installation; the model designation alone does not specify infrared or electronic operation. For the integral drip-fed mechanical automatic-flush version, select B17720.

**Which length and waste outlet options can I select?**

Choose the required length and waste outlet position in the product configurator. The 70 mm waste outlet is available in centre, left-hand and right-hand configurations. Confirm the selected arrangement against the site plumbing layout.

E&OE. Specifications are subject to change without notice.