MODEL SPECIFICATION

B17715(1370R) – Flat Back Urinal 1370mm Right Hand Outlet

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Model	B17715(1370R){PSS}	Published catalogue data	7 Nov 2026

01 Model specification

Flat Back Built-In Urinal, Grade 304 Stainless Steel, 0.9 mm Main Construction; 1370 mm (L) × 811 mm (H) × 300 mm (W), Including Tiling Keys. Right-Hand Pre-Punched Hole for a 1½-Inch BSP Waste Fitting. Concealed Ø28 mm Sparge Pipe with Cover and Connex Inlet; Sloped Drainage Trough with Radiused Corners; Pre-Drilled Wall Mounting Holes in the Top Rear Tiling Key.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	0.9	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.
Height	811	mm	Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.
Width	300	mm	The width of the item typically as measured from front to back.
Mounting Type	Built-in	–	–
Waste Connection	Pre-punched hole for 1½-inch BSP waste fitting	–	–
Sparge Pipe Diameter	28	mm	–
Sparge Pipe Inlet	Connex	–	–
Dimension Basis	Overall dimensions include tiling keys	–	–
Length	1370	mm	The length of the item typically as measured from left to right.
Waste Outlet Orientation	Right Hand	–	–

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

03 Dimensions and mass

PARAMETER	VALUE	UNIT
Length	1370	mm
Width	300	mm
Overall height	811	mm

04 Model and supply data

Parent product	B17715 — Flat Back Urinal
Typical lead time	10–15 working days
Warranty	12 months

05 Specification notes

Configuration description

Flat back built-in urinal, Grade 304 stainless steel, 0.9 mm main construction; 1370 mm (L) × 811 mm (H) × 300 mm (W), including tiling keys. Right-hand pre-punched hole for a 1½-inch BSP waste fitting. Concealed Ø28 mm sparge pipe with cover and Connex inlet; sloped drainage trough with radiused corners; pre-drilled wall mounting holes in the top rear tiling key.

06 Frequently asked questions

How is the urinal installed?

The unit is designed to be built into the wall finish. Tiling keys form part of the unit, and pre-drilled mounting holes in the top rear tiling key allow the urinal to be secured to the wall before the surrounding finish is completed.

What lengths and outlet positions are available?

Choose a length of 915, 1065, 1220, 1370, 1525, 1675, 1830, 2135 or 2440 mm. Each length is available with a left-hand or right-hand waste outlet. There is no centre-outlet version in this range.

Do the overall dimensions include the tiling keys?

Yes. Overall height is 811 mm and overall width is 300 mm. The selected length, height and width include the tiling keys.

What is the main construction material?

The main construction is 0.9 mm thick Grade 304 stainless steel.

What waste connection is provided?

A pre-punched hole is provided for a 1½-inch BSP waste fitting at the selected left-hand or right-hand end. The BSP size describes the nominal waste fitting connection; it is not a measured diameter of the punched hole.

How is flushing water distributed?

A concealed 28 mm diameter sparge pipe with a cover distributes flushing water. The sparge pipe has a Connex inlet connection.

Which flush valve is recommended?

The recommended valve is the Walcro 550URV manual urinal flush valve. It is available as an optional accessory, with one valve recommended per urinal.

What helps with cleaning and drainage?

The sloped drainage trough directs water towards the waste outlet. Radiused internal corners avoid sharp internal crevices and make the trough easier to clean.

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357