

PRODUCT RANGE SPECIFICATION

B17715 – Flat Back Urinal

DOCUMENT SCOPE
Product range

DOCUMENT REFERENCE
B17715{PSS}

DATA STATUS
Published catalogue data

GENERATED ON
18 Oct 2026

Detailed item specifications

Select an item code for its detailed specification sheet, including model dimensions, technical specifications and drawings. For a printed copy, scan the QR code or visit the product page and select the item.

<https://basterfield.co.za/products/b17715-flat-back-urinal#specifications>



01 Product description and specification

Product description	Built-in Grade 304 stainless steel flat back urinal with a covered concealed sparge pipe, radiused drainage trough and left- or right-hand waste outlet.
Short Form Specification	SPECIFICATION USE Use this description when specifying this product range. Built-in flat back urinal in 0.9 mm Grade 304 stainless steel, with tiling keys, top rear mounting holes, concealed Ø28 mm sparge pipe with cover and Connex inlet, and sloped radiused drainage trough. Pre-punched hole for a 1½-inch BSP waste fitting, left- or right-hand. Overall height 811 mm and width 300 mm; length as selected. Dimensions include tiling keys.

02 Models and configurations

ITEM CODE	LENGTH	WASTE OUTLET ORIENTATION
B17715(0915L)	915 mm	Left Hand
B17715(0915R)	915 mm	Right Hand
B17715(1065L)	1065 mm	Left Hand
B17715(1065R)	1065 mm	Right Hand
B17715(1220L)	1220 mm	Left Hand
B17715(1220R)	1220 mm	Right Hand
B17715(1370L)	1370 mm	Left Hand
B17715(1370R)	1370 mm	Right Hand
B17715(1525L)	1525 mm	Left Hand
B17715(1525R)	1525 mm	Right Hand
B17715(1675L)	1675 mm	Left Hand
B17715(1675R)	1675 mm	Right Hand
B17715(1830L)	1830 mm	Left Hand
B17715(1830R)	1830 mm	Right Hand
B17715(2135L)	2135 mm	Left Hand
B17715(2135R)	2135 mm	Right Hand
B17715(2440L)	2440 mm	Left Hand

02 Models and configurations

ITEM CODE	LENGTH	WASTE OUTLET ORIENTATION
B17715(2440R)	2440 mm	Right Hand

03 Functional features

01	Grade 304 stainless steel Main construction in 0.9 mm thick Grade 304 stainless steel.
02	Built-in installation Tiling keys integrate the urinal with the wall finish. Pre-drilled holes in the top rear tiling key provide wall fixing points.
03	Covered concealed sparge pipe A concealed 28 mm diameter sparge pipe with a cover and Connex inlet connection distributes flushing water.
04	Sloped drainage trough The trough slopes towards the waste outlet, with radiused internal corners to aid cleaning and avoid sharp internal crevices.
05	Left or right waste outlet Every standard length is available with a left-hand or right-hand pre-punched hole for a 1½-inch BSP waste fitting.
06	Nine standard lengths Lengths from 915 to 2440 mm share an overall height of 811 mm and width of 300 mm. Overall dimensions include the tiling keys.

04 Application information

Intended applications	Public Restrooms, Restrooms & Ablutions
Industries	Colleges & Universities, Government & Public Sector, Hotels & Lodges, Schools

05 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.