PRODUCT RANGE SPECIFICATION

B17715 – Flat Back Urinal



PRODUCT IMAGE · Range illustration: B17715(1830R) shown. Length and waste outlet orientation depend on the selected model.

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Product range	**B17715{PSS}**	**Published catalogue data**	**7 Nov 2026**

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/b17715-flat-back-urinal#specifications

01 Product description and specification

Product description	Built-in Grade 304 stainless steel flat back urinal with a covered concealed sparge pipe, radiused drainage trough and left- or right-hand waste outlet.
Short Form Specification	**SPECIFICATION USE** Use this description when specifying this product range. Built-in flat back urinal in 0.9 mm Grade 304 stainless steel, with tiling keys, top rear mounting holes, concealed Ø28 mm sparge pipe with cover and Connex inlet, and sloped radiused drainage trough. Pre-punched hole for a 1½-inch BSP waste fitting, left- or right-hand. Overall height 811 mm and width 300 mm; length as selected. Dimensions include tiling keys.

02 Configuration options

Length	9 choices, from 915 mm to 2440 mm
Waste Outlet Orientation	Left Hand; Right Hand

Options vary by model; not every combination is available. Use the product page to select a model.

03 Functional features

01 Grade 304 stainless steel
Main construction in 0.9 mm thick Grade 304 stainless steel.

02 Built-in installation
Tiling keys integrate the urinal with the wall finish. Pre-drilled holes in the top rear tiling key provide wall fixing points.

03 Covered concealed sparge pipe
A concealed 28 mm diameter sparge pipe with a cover and Connex inlet connection distributes flushing water.

04 Sloped drainage trough
The trough slopes towards the waste outlet, with radiused internal corners to aid cleaning and avoid sharp internal crevices.

05 Left or right waste outlet

Every standard length is available with a left-hand or right-hand pre-punched hole for a 1½-inch BSP waste fitting.

06 Nine standard lengths

Lengths from 915 to 2440 mm share an overall height of 811 mm and width of 300 mm. Overall dimensions include the tiling keys.

04 Application information

Intended applications	Public Restrooms, Restrooms & Ablutions
Industries	Colleges & Universities, Government & Public Sector, Hotels & Lodges, Schools

05 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

06 Frequently asked questions

How is the urinal installed?

The unit is designed to be built into the wall finish. Tiling keys form part of the unit, and pre-drilled mounting holes in the top rear tiling key allow the urinal to be secured to the wall before the surrounding finish is completed.

What lengths and outlet positions are available?

Choose a length of 915, 1065, 1220, 1370, 1525, 1675, 1830, 2135 or 2440 mm. Each length is available with a left-hand or right-hand waste outlet. There is no centre-outlet version in this range.

Do the overall dimensions include the tiling keys?

Yes. Overall height is 811 mm and overall width is 300 mm. The selected length, height and width include the tiling keys.

What is the main construction material?

The main construction is 0.9 mm thick Grade 304 stainless steel.

What waste connection is provided?

A pre-punched hole is provided for a 1½-inch BSP waste fitting at the selected left-hand or right-hand end. The BSP size describes the nominal waste fitting connection; it is not a measured diameter of the punched hole.

How is flushing water distributed?

A concealed 28 mm diameter sparge pipe with a cover distributes flushing water. The sparge pipe has a Connex inlet connection.

Which flush valve is recommended?

The recommended valve is the Walcro 550URV manual urinal flush valve. It is available as an optional accessory, with one valve recommended per urinal.

What helps with cleaning and drainage?

The sloped drainage trough directs water towards the waste outlet. Radiused internal corners avoid sharp internal crevices and make the trough easier to clean.

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357