MODEL SPECIFICATION

B17730(1370R) – Wall-Hung Urinal, 1370 mm, Right Outlet

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	B17730(1370R){PSS}	22 Nov 2026

01 Model specification

Wall-Hung Grade 304 Stainless Steel Trough Urinal, 1370 mm Length, Right Hand 40 mm Waste Outlet. Manual Flush Valve and Support Bracket Are Optional and Sold Separately.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Length	1370	mm	The length of the item typically as measured from left to right.
Waste Outlet Orientation	Right Hand	–	–
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Mounting Type	Wall Mounted	–	–
Waste Outlet Diameter	40	mm	–

03 Dimensions and mass

PARAMETER	VALUE	UNIT
Length	1370	mm

04 Model and supply data

Parent product	B17730 — Wall-Hung Stainless Steel Trough Urinal
Typical lead time	10–15 working days
Warranty	12 months

05 Specification notes

Configuration description

The Basterfield B17730(1370R) is a wall-hung Grade 304 stainless steel trough urinal with a 1370 mm length and right hand 40 mm waste outlet. It has a dull polished finish, exposed stainless steel sparge pipe, sloped drip ledge and sound-deadened back panel.

The Walcro 550URV manual urinal flush valve and the 400 or 600 mm finished-height support bracket are optional and priced separately. Select one of each chosen accessory per urinal.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

Short Form Specification

SPECIFICATION USE
Use this description when specifying this model.

Basterfield B17730(1370R); wall-hung Grade 304 stainless steel trough urinal; 1370 mm long; right hand 40 mm waste outlet; dull polished finish; exposed sparge pipe. Flush valve and support bracket optional.

Detailed specification

- Model: B17730(1370R)
- Material: Grade 304 stainless steel
- Length: 1370 mm
- Waste outlet orientation: Right Hand
- Waste outlet diameter: 40 mm
- Mounting: Wall hung
- Flush valve: Optional Walcro 550URV; not included
- Support bracket: Optional 400 or 600 mm finished height; not included

06 Frequently asked questions

Which lengths are available?

Choose 915, 1065, 1220, 1370, 1525, 1675, 1830, 2135 or 2440 mm. Each length is available with a left- or right-hand waste outlet.

What material is the urinal made from?

The B17730 trough urinal is manufactured from Grade 304 stainless steel with a dull polished finish.

How is the urinal mounted?

B17730 is wall hung. Confirm the wall structure, fixing method, mounting height and plumbing positions before installation.

Are midway support brackets required?

Midway support brackets are optional and priced separately. They provide additional support in settings such as schools, where the urinal may be subjected to rough use. If this is not a concern at the installation site and additional support is not required, the brackets may be deselected from the quotation. Select one bracket per urinal when additional support is specified.

Which support bracket height should I choose?

The 400 mm finished-height bracket is intended for junior primary learners. The 600 mm finished-height bracket is intended for senior primary, high school learners and adults.

Is a flush valve included?

No. The Walcro 550URV 20 mm manual urinal flush valve is an optional, separately priced item. Select one valve per urinal when this flushing arrangement is required.

What waste outlet is provided?

The selected model has a 40 mm waste outlet in either a left-hand or right-hand orientation. Match the selected orientation to the site drainage layout. The separate 1½″ BSP waste outlet fitting, compatible P-trap and discharge piping are installation requirements and are excluded from the urinal price unless separately itemised in the quotation.

Do the displayed prices include VAT?

No. Catalogue and quote-template prices are stated excluding VAT.

Which waste fittings and discharge pipework must be supplied separately?

Installation requires one 1½″ BSP waste outlet fitting per urinal, a compatible P-trap (typically PVC), and discharge piping. These components are excluded from the urinal price and must be arranged separately unless expressly included as separate items in the quotation.

What water supply pipework is required for installation?

Provide water supply piping to each flush valve. This pipework is excluded from the urinal price and must be arranged separately. The Walcro 550URV manual flush valve is an optional, separately priced item; select one valve per urinal where this flushing arrangement is required.

E&OE. Specifications are subject to change without notice.