


MODEL SPECIFICATION

B17730(1065R) – WALL HUNG TROUGH URINAL 1067 MM RH



PRODUCT IMAGE

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Model	B17730(1065R){PSS}	Published catalogue data	14 Sep 2026

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Length	1065	mm	The length of the item typically as measured from left to right.
Waste Outlet Orientation	Right Hand	—	—

02 Model and supply data

Parent product	B17730 — Stainless Steel Wall Hung Urinal Manual Flush Valve Type
Typical lead time	10–15 working days
Warranty	12 months

03 Specification notes

Configuration description	Wall-mounted Grade 304 stainless steel trough urinal for use with a manual flush valve in public and commercial washrooms. Selected configuration: Length: 1065 mm; Waste Outlet Orientation: Right Hand.
Short Form Specification	SPECIFICATION USE Use this description when specifying this model. Basterfield B17730(1065R). Wall-mounted Grade 304 stainless steel trough urinal for use with a manual flush valve in public and commercial washrooms. Selected configuration: Length: 1065 mm; Waste Outlet Orientation: Right Hand.
Detailed specification	- Model: B17730(1065R) - Length: 1065 mm - Waste Outlet Orientation: Right Hand

VERIFICATION REQUIRED

Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.