MODEL SPECIFICATION

# B17735(1000L-1000R) – Urinal L-Shape (1000mm (Left) x 1000mm (Right))

| DOCUMENT SCOPE | DOCUMENT REFERENCE | GENERATED ON |
|---|---|---|
| Model | B17735(1000L-1000R){PSS} | 13 Nov 2026 |

## 01 Model specification

Urinal, Stainless Steel Grade 304, 0.9mm Thick, 1000mm (Left) x 1000mm (Right), with Wall-Hung L-Shaped Configuration, Two Sparge Pipes and a Centre 1 1/2-inch BSP Waste Outlet

## 02 Technical specifications

| PARAMETER | VALUE | UNIT | TECHNICAL NOTE |
|---|---|---|---|
| **Material** | Stainless Steel Grade 304 | – | The primary material used in the construction of the item. Certain components may be manufactured from different materials. |
| **Material Thickness** | 0.9 | mm | The thickness of the material used for the item's primary construction. The thickness of individual components may vary. |
| **Waste Outlet Orientation** | Centre | – | – |
| **Left-Hand Length** | 1000 | mm | Viewed from the user side while facing into the corner where the two sections meet, this is the section on your left. Measure along the left-hand wall from the corner junction to the outer end. Select independently from the right-hand length. |
| **Waste Outlet Connection** | 1 1/2-inch BSP | – | – |
| **Right-Hand Length** | 1000 | mm | Viewed from the user side while facing into the corner where the two sections meet, this is the section on your right. Measure along the right-hand wall from the corner junction to the outer end. Select independently from the left-hand length. |
| **Sparge Pipe Quantity** | 2 | – | The number of sparge pipes supplied with the urinal. Each pipe requires its own flush mechanism. |


121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

## 03 Model and supply data

| | |
|---|---|
| **Parent product** | B17735 — Wall Hung Urinal Stainless Steel L-Shape Configuration |
| **Typical lead time** | 10–15 working days |
| **Warranty** | 12 months |

## 04 Specification notes

**Configuration description**

The Basterfield B17735 is a wall-hung, L-shaped corner trough urinal manufactured from 0.9 mm thick Grade 304 stainless steel. The two sections form a corner installation, with a sloping trough that drains to a centre 1 1/2-inch BSP outlet where the sections meet.

Select the left-hand and right-hand lengths independently: 1000, 1200, 1500 or 1800 mm for either side. Equal and unequal side lengths are available, giving 16 size combinations. Left and right are identified from the user side while facing into the corner where the two sections meet. Each side length runs along its wall from that corner to the outer end of the section.

The urinal has two exposed sparge pipes, one for each section. Each pipe requires its own flush mechanism. Walcro 550URV manual flush valves are optional, separately priced accessories: select two valves per urinal, one for each sparge pipe. The flush valves are not included in the urinal configuration.

Selected configuration: left-hand length 1000 mm; right-hand length 1000 mm.

**Short Form Specification**

**SPECIFICATION USE**
Use this description when specifying this model.

Basterfield B17735 wall-hung L-shaped corner trough urinal; 0.9 mm Grade 304 stainless steel; left-hand length 1000 mm and right-hand length 1000 mm; two exposed sparge pipes; sloping trough to a centre 1 1/2-inch BSP outlet at the corner junction. Two Walcro 550URV manual flush valves per urinal are optional and priced separately.

**Detailed specification**

- Model: B17735(1000L-1000R)
- Left-hand length: 1000 mm
- Right-hand length: 1000 mm
- Side identification: From the user side, facing into the corner; each side is measured along its wall from the corner junction to the outer end
- Material: Grade 304 stainless steel
- Material thickness: 0.9 mm
- Mounting: Wall hung
- Layout: L-shaped corner urinal
- Sparge pipes: Two exposed pipes, one per section
- Drainage: Sloping trough to the corner junction where the sections meet
- Waste outlet: Centre, 1 1/2-inch BSP
- Flush mechanisms required: Two, one per sparge pipe
- Optional accessory: Two Walcro 550URV manual flush valves per urinal; separately priced and not included

## 05 Frequently asked questions

**How are the left-hand and right-hand sides identified?**

Stand on the user side and face into the corner where the two urinal sections meet. The section on your left is the left-hand side and the section on your right is the right-hand side. Measure each side along its wall from the corner junction to the outer end.

**Can the two sides have different lengths?**

Yes. Select 1000, 1200, 1500 or 1800 mm independently for each side. All 16 combinations are available, including equal and unequal lengths.

**How many flush valves are required, and are they included?**

Two flush mechanisms are required per urinal because there are two sparge pipes, one for each section. Walcro 550URV manual flush valves are optional, separately priced accessories. Selecting this accessory adds two valves per urinal; they are not included in the urinal configuration.

**What material and waste outlet does B17735 use?**

The urinal is made from 0.9 mm thick Grade 304 stainless steel. Its trough slopes to a centre 1 1/2-inch BSP outlet at the corner junction where the two sections meet.

E&OE. Specifications are subject to change without notice.