
MODEL SPECIFICATION

B17744(B) – Grade 304 Bowl Urinal - Back Entry



PRODUCT IMAGE

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	B17744(B){PSS}	14 Nov 2026

01 Model specification

Basterfield B17744(B) Wall-Mounted Grade 304 Stainless Steel Bowl Urinal to B17744{PSS}, Back Entry, Integral Brackets, Brass Flush Coupling, Flush Spreader and 40 mm Waste Opening. Recommended Optional Flush System: B17744(155UW), Concealed Back Entry, 15 mm, One per Bowl. Accessories Priced Separately.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Flushing Inlet Orientation	Back Entry	–	–
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.

03 Model and supply data

Parent product	B17744 – Bowl Urinals
Typical lead time	10–15 working days
Warranty	12 months

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

04 Specification notes

Configuration description

The Basterfield B17744 is a wall-mounted bowl urinal for individual use in public and commercial washrooms. Grade 304 stainless steel construction, a one-piece bowl, a smooth polished interior and a satin exterior support routine cleaning and daily use. Integral mounting brackets secure the bowl to the wall.

Choose the inlet arrangement to suit the plumbing layout. B17744(B) has back entry for concealed pipework. B17744(T) has top entry for an exposed flush connection. Both models include a brass flush coupling, a flush spreader and a 40 mm waste opening at the base. The waste opening describes the bowl aperture; confirm the required waste fitting and trap when specifying the installation.

For B17744(B), the recommended optional flush system is B17744(155UW), a concealed back-entry 15 mm push-button system. For B17744(T), specify one 04VF_WAL-103LUR Walcro lever-operated valve together with one 04VFP-UR15TP offset flush pipe per bowl. When selecting the top-entry valve, include the offset pipe. Flushing accessories are supplied and priced separately from the bowl.

Typical applications include public restrooms, school and university washrooms, restaurant ablutions and other commercial facilities. Confirm wall support, inlet alignment, waste connections and the selected valve's operating requirements before installation. The bowl urinal is designed and manufactured in South Africa.

Selected model: B17744(B), back entry. Recommended optional flush system: B17744(155UW), concealed back entry, 15 mm, one per bowl.

Short Form Specification

> **SPECIFICATION USE**
> Use this description when specifying this model.

Basterfield B17744(B) wall-mounted Grade 304 stainless steel bowl urinal to B17744{PSS}, back entry, integral brackets, brass flush coupling, flush spreader and 40 mm waste opening. Recommended optional flush system: B17744(155UW), concealed back entry, 15 mm, one per bowl. Accessories priced separately.

Detailed specification

- Model: B17744(B)
- Material: Grade 304 stainless steel
- Mounting: Wall mounted with integral brackets
- Flush inlet: Back entry
- Bowl: One piece, polished interior, satin exterior
- Flush connection: Brass coupling with flush spreader
- Waste opening: 40 mm
- Optional flushing: Recommended optional flush system: B17744(155UW), concealed back entry, 15 mm, one per bowl.
- Bowl origin: South Africa

05 Frequently asked questions

What is the difference between the two models?

B17744(B) has back entry for concealed pipework. B17744(T) has top entry for an exposed flush connection. Both are wall-mounted Grade 304 stainless steel bowl urinals.

Which flush system is recommended for the back-entry model?

Specify the optional B17744(155UW) concealed back-entry 15 mm flush system with B17744(B). It is ordered and priced separately from the bowl.

Which accessories are recommended for the top-entry model?

Specify one 04VF_WAL-103LUR Walcro 103LUR exposed lever-operated valve and one 04VFP-UR15TP offset flush pipe per B17744(T) bowl. If selecting the valve, include the offset pipe as well.

Are the valve and flush pipe included in the bowl price?

No. The published bowl price covers the selected B17744 urinal. The concealed flush system, exposed valve and offset flush pipe are optional items with separate prices.

What material and finish does the bowl have?

The bowl is manufactured from Grade 304 stainless steel with a smooth polished internal surface and satin exterior.

How is the bowl mounted?

It is wall mounted using integral mounting brackets. Check wall support and plumbing positions for the selected entry model before installation.

What waste connection is provided?

The bowl has a 40 mm waste opening at its base. Specify the waste fitting, trap and connection arrangement to suit the installation.

Where can this urinal be used?

Typical uses include public and commercial restrooms, schools, universities and restaurant washrooms. Choose the inlet and flushing arrangement to suit the site.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357