


MODEL SPECIFICATION

B17744(B) – Basterfield B17744(B) Wall-Mounted Grade 304 Stainless Steel Bowl Urinal to B17744{PSS}, Back Entry, Integral Brackets, Brass Flush Coupling, Flush Spreader and 40 mm Waste Opening. Recommended Optional Flush System: B17744(155UW), Concealed Back Entry, 15 mm, One per Bowl. Accessories Priced Separately.



PRODUCT IMAGE

DOCUMENT SCOPE
Model

DOCUMENT REFERENCE
B17744(B){PSS}

DATA STATUS
Published catalogue data

GENERATED ON
4 Oct 2026

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Flushing Inlet Orientation	Back Entry	—	—
Material	Stainless Steel Grade 304	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.

02 Model and supply data

Parent product	B17744 – Bowl Urinals
Typical lead time	10–15 working days
Warranty	12 months

Configuration description	The Basterfield B17744 is a wall-mounted bowl urinal for individual use in public and commercial washrooms. Grade 304 stainless steel construction, a one-piece bowl, a smooth polished interior and a satin exterior support routine cleaning and daily use. Integral mounting brackets secure the bowl to the wall. Choose the inlet arrangement to suit the plumbing layout. B17744(B) has back entry for concealed pipework. B17744(T) has top entry for an exposed flush connection. Both models include a brass flush coupling, a flush spreader and a 40 mm waste opening at the base. The waste opening describes the bowl aperture; confirm the required waste fitting and trap when specifying the installation. For B17744(B), the recommended optional flush system is B17744(155UW), a concealed back-entry 15 mm push-button system. For B17744(T), specify one O4VF_WAL-103LUR Walcro lever-operated valve together with one O4VFP-UR15TP offset flush pipe per bowl. When selecting the top-entry valve, include the offset pipe. Flushing accessories are supplied and priced separately from the bowl. Typical applications include public restrooms, school and university washrooms, restaurant ablutions and other commercial facilities. Confirm wall support, inlet alignment, waste connections and the selected valve's operating requirements before installation. The bowl urinal is designed and manufactured in South Africa. Selected model: B17744(B), back entry. Recommended optional flush system: B17744(155UW), concealed back entry, 15 mm, one per bowl.
Short Form Specification	SPECIFICATION USE Use this description when specifying this model. Basterfield B17744(B) wall-mounted Grade 304 stainless steel bowl urinal to B17744{PSS}, back entry, integral brackets, brass flush coupling, flush spreader and 40 mm waste opening. Recommended optional flush system: B17744(155UW), concealed back entry, 15 mm, one per bowl. Accessories priced separately.
Detailed specification	• Model: B17744(B) • Material: Grade 304 stainless steel • Mounting: Wall mounted with integral brackets • Flush inlet: Back entry • Bowl: One piece, polished interior, satin exterior • Flush connection: Brass coupling with flush spreader • Waste opening: 40 mm • Optional flushing: Recommended optional flush system: B17744(155UW), concealed back entry, 15 mm, one per bowl. • Bowl origin: South Africa

VERIFICATION REQUIRED

Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.