

PRODUCT RANGE SPECIFICATION

B17746 – Conical Bowl Urinal



PRODUCT IMAGE

① Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE

Product range

DOCUMENT REFERENCE

B17746{PSS}

DATA STATUS

Published catalogue data

GENERATED ON

26 Oct 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

<https://basterfield.co.za/products/b17746-conical-bowl-urinal#specifications>



01 Product description and specification

Product description

Wall-mounted conical bowl urinal in 1.2mm Grade 304 stainless steel, with top entry, a fitted spreader and a pre-punched 1½" waste outlet hole. The body shroud does not fully conceal the plumbing.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Basterfield B17746(T) Wall-Mounted Conical Bowl Urinal: Grade 304 Stainless Steel; 1.2mm Construction; Top Entry; Fitted Spreader; Pre-Punched 1½" Waste Outlet Hole; Weight 6.177 kg. The body shroud does not fully conceal the plumbing.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	1.2	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.
Mounting Type	Wall Mounted	—	—
Flushing Inlet Orientation	Top Entry	—	—
Weight	7	kg	—

03 Functional features

01	Conical Bowl An individual conical bowl with a sloping front provides a dedicated urinal position.
02	Grade 304 Stainless Steel Manufactured from 1.2mm Grade 304 stainless steel, with a unit weight of 6.177 kg.
03	Top Entry with Spreader The B17746(T) has a top-entry water inlet and a spreader fitted inside the bowl.
04	Pre-Punched Waste Outlet Hole The 1½" waste outlet hole is pre-punched for coordination with the installation's waste connection.
05	Wall-Mounted Installation Wall mounting keeps the floor immediately below the bowl clear. Coordinate the mounting position with the water supply and waste routing.
06	Plumbing Visibility The body shroud does not fully conceal the plumbing. Consider visible pipework when planning the installation and finished appearance.

04 Application information

Intended applications	Public Restrooms, Restrooms & Ablutions
Industries	Colleges & Universities, General Manufacturing, Government & Public Sector, Hotels & Lodges, Restaurants & Cafés, Schools

05 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.