

PRODUCT RANGE SPECIFICATION

B17747(B) – Shrouded Conical Urinal

DOCUMENT SCOPE Product range	DOCUMENT REFERENCE B17747(B){PSS}	DATA STATUS Published catalogue data	GENERATED ON 14 Sep 2026
---------------------------------	--------------------------------------	---	-----------------------------

01 Product description and specification

Product description	Shrouded conical urinal with a back-entry connection for institutional washrooms requiring an enclosed fixture design. Manufactured from Grade 304 stainless steel, it offers superior hygiene, resistance to corrosion, and long-lasting performance. Its fully shrouded conical design conceals plumbing connections for a clean, modern aesthetic while also deterring tampering and vandalism. The unit features a back-entry flush connection, making it compatible with concealed flush valves, and a 40 mm diameter pre-punched waste outlet for reliable drainage. Stainless steel’s non-porous surface ensures it is quick and easy to clean, making it as hygienic as ceramic but significantly more durable and resistant to shock and impact. With a height of 733 mm and a width of 313 mm, the B17747 urinal is compact yet robust, suited to schools, public restrooms, stadiums, factories, transport hubs, and any arduous-use environments where both aesthetics and durability are key. Lightweight in construction yet highly resilient, this unit combines practicality with a sleek, modern profile.
Short Form Specification	SPECIFICATION USE Use this description when specifying this product range. Basterfield B17747(B). Shrouded Conical Urinal. The unit features a back-entry flush connection, making it compatible with concealed flush valves, and a 40 mm diameter pre-punched waste outlet for reliable drainage.

02 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B17747(B)	SHROUDED CONICAL URINAL TO B17747(PSS)	Standard configuration

03 Application information

Intended applications	Public Restrooms
Industries	Government & Public Sector

04 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

Product drawings and images**PRODUCT IMAGE**

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.