

PRODUCT RANGE SPECIFICATION

B17770 – Square Bowl Urinals



PRODUCT IMAGE

① Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE

Product range

DOCUMENT REFERENCE

B17770{PSS}

DATA STATUS

Published catalogue data

GENERATED ON

4 Oct 2026

01 Product description and specification

Product description

Square bowl urinal for public and institutional washrooms. Specify the required fixture and plumbing configuration for the installation.

Manufactured in South Africa from Grade 304 (18/10) satin polished stainless steel, the B17770 offers superior resistance to corrosion, impact, and vandalism, while maintaining a hygienic, non-porous surface that is easy to clean and maintain.

Available in top-entry and back-entry flushing configurations, the urinal includes a 1/2" spreader inlet for connection to a flush system (not included as standard). Waste outlet and trap are not supplied by default but are available on request.

The B17770 is designed for secure, concealed installation. Offset wall brackets with tiling keys and Ø8 mm pre-punched mounting holes support hidden, tamper-resistant fixing behind tiles or plaster. Compact dimensions make the unit suitable for installations where space efficiency and durability are critical.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Basterfield B17770. Square Bowl Urinals. Flushing Inlet Orientation: Back Entry, Top Entry. Available in top-entry and back-entry flushing configurations, the urinal includes a 1/2" spreader inlet for connection to a flush system (not included as standard). Offset wall brackets with tiling keys and Ø8 mm pre-punched mounting holes support hidden, tamper-resistant fixing behind tiles or plaster.

02 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B17770(B)	Square Bowl S/Steel Aisi 304 Back Entry	Flushing Inlet Orientation: Back Entry
B17770(T)	Square Bowl Urinal 304 to B17770(PSS)	Flushing Inlet Orientation: Top Entry

03 Application information

Intended applications

Public Restrooms

Industries

Government & Public Sector

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.