
MODEL SPECIFICATION

B22315(900) – Shower Seat Foldable Wall-Mounted 900mm Length



PRODUCT IMAGE

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	B22315(900){PSS}	14 Nov 2026

01 Model specification

Shower Seat, Stainless Steel Grade 304, 900mm Length, with Foldable Slatted Seat, Satin Polished Finish and Supplied Wall-Mounting Brackets

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Length	900	mm	The length of the item typically as measured from left to right.

03 Model and supply data

Parent product	B22315 — Foldable Wall Mounted Shower Seat
Typical lead time	10–15 working days
Warranty	12 months

04 Specification notes

Configuration description

This 900mm B22315 shower seat is made from Grade 304 stainless steel with a satin-polished finish. The slatted seat drains water through the gaps and folds away for standing use. Supplied wall-mounting brackets provide four mounting points. Confirm the supporting wall and fixing requirements for the installation.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this model.

Basterfield B22315(900). Length: 900mm; Material: Stainless Steel Grade 304; Finish: Satin Polished; Seat: Foldable and Slatted; Support: Supplied Wall-Mounting Brackets; Mounting Points: Four.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

Detailed specification	• Item Code: B22315(900) • Length: 900mm • Material: Stainless Steel Grade 304 • Finish: Satin Polished • Seat: Foldable and Slatted • Support: Supplied Wall-Mounting Brackets • Mounting Points: Four

05 Frequently asked questions

Which lengths are available?

Choose a 450mm, 600mm or 900mm seat length.

What material and finish are used?

The seat is made from Grade 304 stainless steel with a satin-polished finish.

Does the seat fold away?

Yes. The seat folds away to make room for standing use of the shower.

What mounting arrangement is supplied?

Heavy-duty wall-mounting brackets with four mounting points are supplied. Confirm the supporting wall and fixing requirements for the installation when requesting a quotation.

How does water drain from the seat?

The slatted seat allows water to pass through the gaps between the slats.

E&OE. Specifications are subject to change without notice.