MODEL SPECIFICATION

B22320(FM-112-0900) – Floor-Mounted Scrub-Up Sink, 900 mm, 1.2 mm Thick



PRODUCT IMAGE

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	B22320(FM-112-0900){PSS}	14 Nov 2026

01 Model specification

Floor-Mounted Surgeon Scrub-Up Sink, 900 mm Long, 1.2 mm Thick Grade 304 Stainless Steel.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Length	900	mm	The length of the item typically as measured from left to right.
Material Thickness	1.2	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.

03 Model and supply data

Parent product	B22320(FM) — Floor-Mounted Surgeon Scrub-Up Sink
Typical lead time	10–15 working days
Warranty	24 months

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

04 Specification notes

Configuration description

The Basterfield B22320(FM-112-0900) is a 900 mm long floor-mounted surgeon scrub-up sink manufactured from 1.2 mm thick Grade 304 stainless steel. It has a polished satin finish and double-walled, pressed and welded construction for rigidity and routine cleaning in clinical handwashing areas.

Floor-mounting brackets support the unit. A 250 x 250 mm access panel provides access to plumbing connections for servicing, and a rear splashback helps protect the wall from splashing.

This model has one 40 mm diameter drainage outlet. Confirm the required tapware and plumbing arrangement when requesting a quotation.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this model.

Basterfield B22320(FM-112-0900) floor-mounted surgeon scrub-up sink, 900 mm long, in 1.2 mm Grade 304 stainless steel. Polished satin finish; double-walled, pressed and welded construction; rear splashback; floor-mounting brackets; 250 x 250 mm plumbing access panel; one 40 mm diameter drainage outlet. Tapware and plumbing arrangement to be confirmed in the quotation.

Detailed specification

- Model: B22320(FM-112-0900)
- Material: Grade 304 stainless steel
- Material thickness: 1.2 mm
- Finish: polished satin
- Construction: double-walled, pressed and welded
- Length: 900 mm
- Mounting: floor-mounted with floor-mounting brackets
- Plumbing access panel: 250 x 250 mm
- Splashback: rear
- Drainage: one 40 mm diameter drainage outlet
- Tapware and plumbing arrangement: confirm in quotation

05 Frequently asked questions

What lengths are available?

The B22320(FM) range has six standard lengths: 900, 1200, 1500, 1800, 2100 and 2400 mm. Each length is available in both 1.2 mm and 1.5 mm material thickness, giving 12 published configurations.

What material and finish does the sink use?

The sink is manufactured from Grade 304 stainless steel with a polished satin finish. The trough has double-walled, pressed and welded construction, with a choice of 1.2 mm or 1.5 mm material thickness.

How can the plumbing connections be accessed?

A 250 x 250 mm access panel provides access to plumbing connections for maintenance and servicing.

How many drainage outlets does each model have?

The 900, 1200, 1500 and 1800 mm models have one 40 mm diameter drainage outlet. The 2100 and 2400 mm models have two 40 mm diameter outlets. The outlet arrangement is the same for both material thickness options.

How is the sink mounted?

The B22320(FM) is a floor-mounted unit supported by floor-mounting brackets. It also has a rear splashback.

What tapware can be specified?

The range can be specified with elbow-operated medical mixers or sensor-activated tapware. Confirm the tapware type and what is included in the supply when requesting a quotation.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357