MODEL SPECIFICATION

B22320(WM-112-1500) – Wall-Mounted Scrub-Up Sink, 1500 mm, 1.2 mm Thick



PRODUCT IMAGE

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	B22320(WM-112-1500){PSS}	14 Nov 2026

01 Model specification

Wall-Mounted Surgeon Scrub-Up Sink, 1500 mm Long, 1.2 mm Thick Grade 304 Stainless Steel.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Length	1500	mm	The length of the item typically as measured from left to right.
Material Thickness	1.2	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.

03 Model and supply data

Parent product	B22320(WM) — Wall-Mounted Surgeon Scrub-Up Sink
Typical lead time	10–15 working days
Warranty	24 months

04 Specification notes

Configuration description

The Basterfield B22320(WM-112-1500) is a 1500 mm long wall-mounted surgeon scrub-up sink manufactured from 1.2 mm thick Grade 304 stainless steel. It has a polished satin finish and double-walled, pressed and welded construction for rigidity and routine cleaning in clinical handwashing areas.

This model is 455 mm wide, with a trough height of 620 mm excluding the integral 150 mm splashback. Bracket-supported wall mounting keeps the floor beneath the trough clear for cleaning, while the splashback helps protect the wall from water splashes.

This model has one 40 mm diameter drainage outlet. Confirm the required tapware and plumbing arrangement when requesting a quotation. Manufactured in South Africa.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this model.

Basterfield B22320(WM-112-1500) wall-mounted surgeon scrub-up sink, 1500 mm long x 455 mm wide, in 1.2 mm Grade 304 stainless steel. Trough height: 620 mm excluding the integral 150 mm splashback. Polished satin finish; double-walled, pressed and welded construction; bracket-supported wall mounting; one 40 mm diameter drainage outlet. Manufactured in South Africa.

Detailed specification

- Model: B22320(WM-112-1500)
- Material: Grade 304 stainless steel
- Material thickness: 1.2 mm
- Finish: polished satin
- Construction: double-walled, pressed and welded
- Length: 1500 mm
- Overall width: 455 mm
- Trough height: 620 mm excluding splashback
- Integral splashback height: 150 mm
- Mounting: wall-mounted with bracket support
- Drainage: one 40 mm diameter drainage outlet
- Country of manufacture: South Africa

05 Frequently asked questions

What lengths are available?

The B22320(WM) range has six standard lengths: 900, 1200, 1500, 1800, 2100 and 2400 mm. Each length is available in both 1.2 mm and 1.5 mm material thickness, giving 12 published configurations.

What material and finish does the sink use?

The sink is manufactured from Grade 304 stainless steel with a polished satin finish. The trough has double-walled, pressed and welded construction, with a choice of 1.2 mm or 1.5 mm material thickness.

What are the width, trough height and splashback height?

All standard models are 455 mm wide. The trough height is 620 mm, excluding the integral 150 mm splashback. Length varies with the model selected.

How many drainage outlets does each model have?

The 900, 1200, 1500 and 1800 mm models have one 40 mm diameter drainage outlet. The 2100 and 2400 mm models have two 40 mm diameter outlets. The outlet arrangement is the same for both material thickness options.

How is the sink mounted?

The B22320(WM) uses a bracket-supported wall-mounted installation. This leaves the floor beneath the trough clear for cleaning.

Where is the B22320(WM) manufactured?

The B22320(WM) wall-mounted surgeon scrub-up sink is manufactured in South Africa.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357