PRODUCT RANGE SPECIFICATION

B22324 – Foot-Activated Surgeon's Scrub-Up Trough



PRODUCT IMAGE · Two-station 1500mm model shown.

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Product range	**B22324{PSS}**	**23 Nov 2026**

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/b22324-foot-activated-surgeons-scrub-up-trough#specifications

01 Product description and specification

Product description	Grade 304 stainless steel surgeon scrub-up troughs with foot-operated water controls and 1.5mm material thickness. Choose two stations at 1200mm or 1500mm, three at 1800mm, or four at 2400mm.
Short Form Specification	**SPECIFICATION USE** Use this description when specifying this product range. Foot-Activated Surgeon Scrub-Up Trough, Stainless Steel Grade 304, 1.5mm Material Thickness, with Raised Rear Splashback. Standard Configurations: 1200mm and 1500mm with Two Stations; 1800mm with Three Stations; 2400mm with Four Stations.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	1.5	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.
Activation Mechanism	Foot Activated	–	–

03 Configuration options

Length	1200 mm; 1500 mm; 1800 mm; 2400 mm

Options vary by model; not every combination is available. Use the product page to select a model.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

04 Functional features

01 Foot-Activated Water Control
Operate the scrub-up water outlets using the foot controls.

02 Grade 304 Stainless Steel
The scrub-up trough is manufactured from Grade 304 stainless steel.

03 1.5mm Material Thickness
All four lengths in this range use 1.5mm stainless steel.

04 Four Standard Lengths
Choose 1200mm, 1500mm, 1800mm or 2400mm to suit the available installation space.

05 Two, Three or Four Stations
The 1200mm and 1500mm models have two stations, the 1800mm model has three, and the 2400mm model has four.

06 Raised Rear Splashback
A raised rear splashback forms the back of the wash area.

05 Application information

Intended applications	Hands-Free Handwashing, Hospital Sinks
Industries	Hospitals & Clinics

06 Supply and support

Typical lead time	10–15 working days
Warranty	24 months

07 Frequently asked questions

Which lengths and station counts are available?
The standard configurations are 1200mm with two stations, 1500mm with two stations, 1800mm with three stations and 2400mm with four stations.

How is the water operated?
B22324 uses foot activation to operate the scrub-up water outlets. Confirm the control and tap arrangement for the selected model in your quotation.

What material and thickness are used?
These scrub-up troughs use Grade 304 stainless steel with a material thickness of 1.5mm.

Which model is shown in the product image?
The advertising image shows the two-station 1500mm model. The 1800mm and 2400mm models have three and four stations respectively, so their proportions and station arrangements differ.

Are the 1200mm and 1500mm models both two-station units?
Yes. Both the 1200mm and 1500mm configurations have two stations. Select the length to suit the available space.

Are mixing valves, waste fittings and installation included?
Confirm the required water-temperature-control equipment, waste fittings and installation scope when requesting a quotation. The selected item description and accepted quotation define what will be supplied.

Can I request a different configuration?
The published standard pairings are listed in the size selector. Include any other length or station-count requirement in your enquiry so it can be checked before an order is accepted.

How do I request pricing and delivery information?

Select the required length and quantity, then add the model to your quote request. Include your delivery location and installation requirements so the quotation can confirm the specification, price and timing.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357