

MODEL SPECIFICATION

B22328(G1-SL) – Medical Wash Hand Basin Stainless Steel Grade 304, 1.2mm Thick, 500mm (L) × 420mm (W) with 440mm (L) × 310mm (W) × 150mm (D) Bowl, 150mm Rear Splashback, Two Ø22mm Tap Holes at 180mm Centres, 40mm Waste Outlet and Stainless Steel Gallows Brackets with Front Support Legs and Adjustable Feet. Basin and Bracket Height: 500mm



PRODUCT IMAGE

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Model	B22328(G1-SL){PSS}	Published catalogue data	5 Oct 2026

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Front Support Legs	Yes	—	—
Material	Stainless Steel Grade 304	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	1.2	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.
Length	500	mm	The length of the item typically as measured from left to right.
Width	420	mm	The width of the item typically as measured from front to back.
Number of Bowls	1	—	—
Bowl Length	440	mm	The length of the bowl typically as measured from left to right.
Bowl Width	310	mm	—

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Bowl Depth	150	mm	—
Splashback Height	150	mm	Height of the splashback above the tabletop or working surface.
Mounting Type	Stainless Steel Gallows Brackets	—	—
Basin and Bracket Height	500	mm	Vertical dimension from the top of the splashback to the bottom of the wall-mounting brackets. The installed height above the floor is set during installation.
Turndown Edge	26	mm	—
Bracket Tube Section	25 × 25mm square stainless steel tube	—	—
Bracket Mounting Hole Pitch	215	mm	Vertical centre-to-centre spacing of the mounting holes on each wall bracket.
Waste Outlet Diameter	40	mm	—
Mounting Hole Diameter	10	mm	Diameter of the pre-cut mounting holes.
Tap Hole Provision	Two Ø22mm holes at 180mm centres in the splashback	—	Two pre-punched tap holes in the splashback for a separately selected medical mixer.
Tapware Supply	Borras medical mixer optional; not included	—	—

02 Model and supply data

Parent product	B22328(G1) – Medical Wash Hand Basin
Typical lead time	10–15 working days
Warranty	24 months

Configuration description	The B22328(G1-SL) medical wash hand basin provides a wall-mounted handwashing point for hospitals, clinics, dental surgeries, veterinary practices and laboratory areas. It is manufactured from 1.2 mm Grade 304 stainless steel. A 150 mm rear splashback protects the wall behind the basin. Two pre-punched Ø22 mm tap holes at 180 mm centres accommodate a medical mixer. The Borrás medical mixer with wall and deck mounting kit is available as an optional accessory and is supplied separately from the basin. This configuration includes stainless steel gallows brackets and stainless steel front support legs with adjustable feet. The basin has a 26 mm turndown edge and a 40 mm waste outlet. The wall-mount assembly measures 500 mm from the top of the splashback to the bottom of the brackets. Set the installed basin height and specify the waste fitting, trap and plumbing connections for the installation.
Short Form Specification	SPECIFICATION USE Use this description when specifying this model. Basterfield B22328(G1-SL) wash hand basin in 1.2 mm Grade 304 stainless steel, 500 mm (L) x 420 mm (W), with a 440 mm (L) x 310 mm (W) x 150 mm (D) bowl, 150 mm rear splashback and 26 mm turndown edge. Two Ø22 mm tap holes at 180 mm centres in the splashback; 40 mm waste outlet. Include 25 x 25 mm square tubular stainless steel gallows brackets with a 215 mm vertical mounting-hole pitch. Basin and bracket assembly height 500 mm; installed height to suit the installation. This configuration includes stainless steel gallows brackets and stainless steel front support legs with adjustable feet. Borrás medical mixer optional and supplied separately. Waste fitting, trap and pipework to be specified.
Detailed specification	• Model: B22328(G1-SL) • Material: Stainless Steel Grade 304 • Material Thickness: 1.2 mm • Basin Dimensions: 500 mm (L) x 420 mm (W) • Number of Bowls: 1 • Bowl Dimensions: 440 mm (L) x 310 mm (W) x 150 mm (D) • Splashback Height: 150 mm • Turndown Edge: 26 mm • Mounting: Stainless steel gallows brackets • Bracket Tube: 25 x 25 mm square stainless steel • Bracket Mounting-Hole Pitch: 215 mm vertically • Basin and Bracket Assembly Height: 500 mm; height above the floor set during installation • Front Support Legs: Included, with adjustable feet • Mounting Holes: Ø10 mm • Tap Holes: Two Ø22 mm holes at 180 mm centres in the splashback • Waste Outlet: 40 mm • Tapware Supply: Borrás medical mixer with wall and deck mounting kit optional; not included • Waste fitting, trap and connecting pipework: Specify with quotation

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.