MODEL SPECIFICATION

B22330(R-1830-HLC) – Sink Bedpan and Wash-Up 1830mm Length Right Hand

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	B22330(R-1830-HLC){PSS}	15 Nov 2026

01 Model specification

Combination Bedpan and Wash-Up Sink, Grade 304 Stainless Steel, 1830mm Length, with Right Hand Sluice Outlet, Gallows Brackets, Tapware Package #2 and High-Level Cistern

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Length	1830	mm	The length of the item typically as measured from left to right.
Bowl Orientation	Right Hand	–	Left-hand or right-hand position of the sluice outlet on the combination unit.
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.

03 Dimensions and mass

PARAMETER	VALUE	UNIT
Length	1830	mm

04 Model and supply data

Parent product	B22330(HLC) — Combination Bedpan & Wash-Up Sink with High-Level Cistern — Package #2
Typical lead time	10–15 working days
Warranty	24 months

05 Specification notes

Configuration description

Combination bedpan and wash-up sink, 1830 mm long, right hand sluice outlet, on gallows brackets, with tapware package #2, high-level cistern.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this model.

Basterfield B22330(R-1830-HLC). Combination bedpan and wash-up sink, 1830 mm long, right hand sluice outlet, on gallows brackets, with tapware package #2, high-level cistern.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

Detailed specification

- Length: 1830 mm
- Sluice outlet position: Right Hand
- Tapware package: #2
- Flushing: high-level cistern
- Mounting: gallows brackets
- Material: Grade 304 stainless steel
- Finish: satin
- Sluice outlet: 110 mm
- Wash-up outlet: 40 mm, draining internally to sluice outlet

06 Frequently asked questions

Which lengths are available?

The standard B22330 lengths are 1830, 2135 and 2440 mm. Each length is available with a left- or right-hand sluice outlet.

Can I choose a left- or right-hand outlet?

Yes. Every standard length is available with either a left-hand or right-hand sluice outlet.

What is the difference between T3, T4 and HLC?

T3 includes tapware package #3 with a 104 flush valve. T4 includes the same sink, T3 tapware and 104 flush valve, plus an elbow-operated hot-and-cold medical mixer as part of package #4. HLC uses tapware package #2 with a high-level cistern. All three packages are available in the same standard lengths and outlet positions.

Where is this combination sink used?

The B22330 combines bedpan sluicing and an adjacent wash-up sink for sluice rooms, also called dirty utility rooms, in hospitals, clinics, aged-care facilities and nursing homes.

How is the sink mounted?

The unit is supplied on gallows brackets.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357