MODEL SPECIFICATION

B22330(R-1830-T3) – Combination Bedpan & Wash Up Sink 1830mm Right

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	B22330(R-1830-T3){PSS}	27 Nov 2026

01 Model specification

Combination Bedpan and Wash-Up Sink, 1830 mm Long, Right Hand Sluice, on Gallows Brackets, with Tapware Package #3, 104 Flush Valve.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Length	1830	mm	The length of the item typically as measured from left to right.
Bowl Orientation	Right Hand	–	Left-hand or right-hand position of the sluice outlet on the combination unit.

03 Dimensions and mass

PARAMETER	VALUE	UNIT
Length	1830	mm

04 Model and supply data

Parent product	B22330(T3) — Combination Bedpan & Wash-Up Sink with Tapware Package #3
Typical lead time	10–15 working days
Warranty	24 months

05 Specification notes

Configuration description

Combination bedpan and wash-up sink, 1830 mm long, right hand sluice, on gallows brackets, with tapware package #3, 104 flush valve.

Short Form Specification

> **SPECIFICATION USE**
> Use this description when specifying this model.

Basterfield B22330(R-1830-T3). Combination bedpan and wash-up sink, 1830 mm long, right hand sluice, on gallows brackets, with tapware package #3, 104 flush valve.

Detailed specification

- Length: 1830 mm
- Sluice position: Right Hand
- Tapware package: #3
- Flushing: 104 flush valve
- Mounting: gallows brackets

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

06 Frequently asked questions

Which lengths are available?

The standard B22330 lengths are 1830, 2135 and 2440 mm. Each length is available with a left- or right-hand sluice outlet.

Can I choose a left- or right-hand outlet?

Yes. Every standard length is available with either a left-hand or right-hand sluice outlet.

What is the difference between T3, T4 and HLC?

T3 includes tapware package #3 with a 104 flush valve. T4 includes the same sink, T3 tapware and 104 flush valve, plus an elbow-operated hot-and-cold medical mixer as part of package #4. HLC uses tapware package #2 with a high-level cistern. All three packages are available in the same standard lengths and outlet positions.

Where is this combination sink used?

The B22330 combines bedpan sluicing and an adjacent wash-up sink for sluice rooms, also called dirty utility rooms, in hospitals, clinics, aged-care facilities and nursing homes.

How is the sink mounted?

The unit is supplied on gallows brackets.

E&OE. Specifications are subject to change without notice.