

MODEL SPECIFICATION

**B22336(RTG-112-1200-106) –
B22336(RTG-112-1200-106)
Combination Slop Hopper Sink,
Right-Hand Hopper, 1200 mm (L),
with 106 Flush Valve and Bucket
Grid.**



PRODUCT IMAGE : Right-hand hopper configuration
with 106 flush valve and bucket grid

DOCUMENT SCOPE Model	DOCUMENT REFERENCE B22336(RTG-112-1200-106) {PSS}	DATA STATUS Published catalogue data	GENERATED ON 4 Oct 2026
-------------------------	---	---	----------------------------

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Bucket Grid	Yes	–	–
Inlet Valve Orientation	Right	–	–
Length	1200	mm	The length of the item typically as measured from left to right.
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	1.2	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.

02 Dimensions and mass

PARAMETER	VALUE	UNIT
Length	1200	mm

03 Model and supply data

Parent product	B22336(112-1200-106) – 1200 mm Slop Hopper and Wash Basin with 106 Flush Valve
Typical lead time	10–15 working days
Warranty	24 months

Configuration description	This 1200 mm combination slop hopper sink has a right-hand hopper and integrated basin. The main body is manufactured from 1.2 mm Grade 304 stainless steel. The hopper supports efficient waste removal and is supplied with a 106 flush valve. This configuration includes the bucket grid.
Short Form Specification	SPECIFICATION USE Use this description when specifying this model. Basterfield B22336(RTG-112-1200-106). 1200 mm combination slop hopper sink; right-hand hopper; 1.2 mm Grade 304 stainless steel main body; 106 flush valve; bucket grid included.
Detailed specification	• Model: B22336(RTG-112-1200-106) • Length: 1200 mm • Main body: 1.2 mm Grade 304 stainless steel • Hopper orientation: Right-Hand • Combination basin: Included • Flush valve: 106 • Bucket grid: Included

VERIFICATION REQUIRED

Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.