

PRODUCT RANGE SPECIFICATION

B22336(112-1200-106) – 1200 mm Slop Hopper and Wash Basin with 106 Flush Valve

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Product range	B22336(112-1200-106){PSS}	Published catalogue data	14 Sep 2026

01 Product description and specification

Product description	1200 mm combination slop hopper and wash basin with a 106 flush valve for healthcare and institutional sluice rooms. Precision-manufactured from Grade 304 stainless steel, this 1200 mm-long unit combines a slop hopper and wash basin into a single, easy-to-clean assembly that withstands frequent and intensive use. The integrated slop hopper features a flushing rim and top-entry Walcro 106 Flush Valve for reliable and sanitary waste disposal. The position of the hopper and cistern can be tailored to suit project requirements, with left or right-hand configurations available. The hopper connects directly to standard 110 mm waste systems, and an optional hinged bucket grid can be included for additional practicality. Adjacent to the hopper, the wash basin incorporates a 40 mm waste outlet for effective drainage and easy handwashing. Optional tapware can be specified as required. To the right of the basin, a practical draining area supports workflow efficiency by providing a dedicated space for drying or staging. Measuring 1200 mm in length, this model is suited to installations where space is at a but uncompromising hygiene and durability are essential. It is supplied with robust wall-mounting brackets for secure installation and features a 110 mm high rear splashback to protect walls and aid infection control.
Short Form Specification	SPECIFICATION USE Use this description when specifying this product range. Basterfield B22336(112-1200-106). 1200 mm Slop Hopper and Wash Basin with 106 Flush Valve. Inlet Valve Orientation: Left, Right. Bucket Grid: No, Yes. Precision-manufactured from Grade 304 stainless steel, this 1200 mm-long unit combines a slop hopper and wash basin into a single, easy-to-clean assembly that withstands frequent and intensive use. The hopper connects directly to standard 110 mm waste systems, and an optional hinged bucket grid can be included for additional practicality.

02 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B22336(LT-112-1200-106)	B22336(LT-112-1200-106) Combination Slop Hopper and Wash Basin 1200mm (L) with Left-Hand Hopper and 106 Flush Valve Inlet Valve Orientation: Left. Bucket Grid: No.	Bucket Grid: No Inlet Valve Orientation: Left

02 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B22336(LTG-112-1200-106)	B22336(LTG-112-1200-106) Combination Slop Hopper and Wash Basin 1200mm (L) with Left-Hand Hopper, 106 Flush Valve and Bucket Grid Inlet Valve Orientation: Left. Bucket Grid: Yes.	Bucket Grid: Yes Inlet Valve Orientation: Left
B22336(RT-112-1200-106)	B22336(RT-112-1200-106) Combination Slop Hopper and Wash Basin 1200mm (L) with Right-Hand Hopper and 106 Flush Valve Inlet Valve Orientation: Right. Bucket Grid: No.	Bucket Grid: No Inlet Valve Orientation: Right
B22336(RTG-112-1200-106)	B22336(RTG-112-1200-106) Combination Slop Hopper and Wash Basin 1200mm (L) with Right-Hand Hopper, 106 Flush Valve and Bucket Grid Inlet Valve Orientation: Right. Bucket Grid: Yes.	Bucket Grid: Yes Inlet Valve Orientation: Right

03 Application information

Intended applications	Sluice Rooms (Dirty Utility Rooms)
Industries	Hospitals & Clinics

04 Supply and support

Typical lead time	10-15 working days
Warranty	12 months

Product drawings and images**PRODUCT IMAGE**

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.