

PRODUCT RANGE SPECIFICATION

B22360(BG) – Back-Entry Wall-Mounted Stainless Steel Slop Hopper with Grid

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Product range	B22360(BG){PSS}	Published catalogue data	14 Sep 2026

01 Product description and specification

Product description	Wall-mounted stainless steel slop hopper with a bucket grid and back-entry flushing connection for institutional sluice rooms. Manufactured from 1.2 mm thick AISI 304 stainless steel, the unit features a pressed bowl with fully welded seams, providing a durable and hygienic solution for waste disposal. The entire assembly is polished to a satin finish, ensuring both corrosion resistance and ease of cleaning. The B22360(BG) model is configured for back-entry flushing, offering flexible plumbing integration for retrofits or installations with concealed services. The flush valve is not supplied as standard with this unit, but compatible flush valve options (including manual and sensor types) can be specified upon request. The hopper incorporates a hinged waste grid for convenience and is wall-mounted using heavy-duty 38 × 38 mm stainless steel tubular gallows brackets for secure and long-lasting installation. The waste outlet is sized to accept a 100 mm diameter trap, accommodating standard plumbing connections. Construction and features • Grade: AISI 304 stainless steel. • Thickness: 1.2 mm. • Finish: Satin polish for hygiene and corrosion resistance. • Flushing Type: Back-entry configuration (flush valve optional). • Grid: Hinged at the rear for access and waste handling. • Waste Outlet: Sized for 100 mm diameter trap. • Mounting: Wall-supported using 38 × 38 mm stainless steel gallows brackets. Flush Mechanism: Not included by default. Compatible flush valve options available upon request. Engineered for reliability in high-usage environments, the B22360(BG) model combines practical design with durable construction for long-term performance in sanitation-critical applications.
---------------------	--

Short Form Specification	SPECIFICATION USE Use this description when specifying this product range. Basterfield B22360(BG). Back-Entry Wall-Mounted Stainless Steel Slop Hopper with Grid. Manufactured from 1.2 mm thick AISI 304 stainless steel, the unit features a pressed bowl with fully welded seams, providing a durable and hygienic solution for waste disposal. The hopper incorporates a hinged waste grid for convenience and is wall-mounted using heavy-duty 38 × 38 mm stainless steel tubular gallows brackets for secure and long-lasting installation.
--------------------------	---

02 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B22360(BG)	B22360(BG) SLOP HOPPER BACK ENTRY FLUSH PIPEAND GRID TO B22360(BG) (PSS)	Standard configuration

03 Application information

Intended applications	Sluice Rooms (Dirty Utility Rooms)
Industries	Hospitals & Clinics

04 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

Product drawings and images



PRODUCT IMAGE

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.