

PRODUCT RANGE SPECIFICATION

B22360(NG) – Wall Mounted Slop Hopper Sink Neutral-Type with Grid

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Product range	B22360(NG){PSS}	Published catalogue data	14 Sep 2026

01 Product description and specification

Product description

Wall-mounted neutral-type slop hopper with a bucket grid for waste disposal and utensil handling in institutional sluice rooms.

Constructed from 1.2 mm thick AISI 304 stainless steel and polished to a satin finish, this unit is engineered for easy maintenance, high durability, and resistance to corrosion in high-use settings.

Unlike other models, the neutral variant does not include a flush rim or integrated flush inlet, making it suited to installations where external or manual cleaning systems are in place, or where customized plumbing solutions are required. This design offers greater flexibility for non-standard or low-water-use environments.

It includes a rear-hinged grid for convenient waste handling and is supported by industrial-grade 38 × 38 mm stainless steel gallows brackets to ensure a stable and long-lasting wall installation. The outlet is designed to accommodate a 100 mm diameter trap, meeting standard waste plumbing requirements.

Product Specifications:

- Material: stainless steel AISI 304.
- Material Thickness: 1.2 mm.
- Finish: Satin polish.
- Flushing: No built-in flush rim or inlet (neutral type).
- Grid: Hinged at the rear.
- Waste Outlet: Compatible with 100 mm trap.
- Wall Fixing: 38 × 38 mm stainless steel tubular gallows brackets.
- Intended Use: Hospitals, clinics, institutions, and custom sanitation setups.

This no-flush design offers maximum installation versatility and is a reliable choice where water-fed flushing is either not required or manually managed.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Basterfield B22360(NG). Wall Mounted Slop Hopper Sink Neutral-Type with Grid. Constructed from 1.2 mm thick AISI 304 stainless steel and polished to a satin finish, this unit is engineered for easy maintenance, high durability, and resistance to corrosion in high-use settings. The outlet is designed to accommodate a 100 mm diameter trap, meeting standard waste plumbing requirements.

02 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B22360(NG)	SLOP HOPPER AND GRID (NO FLUSH RIM OR PIPE)	Standard configuration

03 Application information

Intended applications	Sluice Rooms (Dirty Utility Rooms)
Industries	Hospitals & Clinics

04 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

Product drawings and images



VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.