

PRODUCT RANGE SPECIFICATION

B22360(NGS) – Slop Hopper Neutral Grid with Stand



PRODUCT IMAGE

① Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE
Product range

DOCUMENT REFERENCE
B22360(NGS){PSS}

DATA STATUS
Published catalogue data

GENERATED ON
4 Oct 2026

01 Product description and specification

Product description

Grade 304 stainless steel neutral slop hopper with a hinged bucket grid and supporting stand. Supplied without an integral flushing system.

The pressed and welded stainless steel construction has smoothly finished welds and a satin finish. The hinged bucket grid supports receptacles over the hopper and lifts for cleaning access.

The neutral hopper excludes the flushing mechanism, flush inlet and integral flushing rim. The supporting stand uses 40 × 40 mm square stainless steel tube legs.

Intended for waste disposal in hospital, clinic and institutional sluice rooms.

Compare the stainless steel slop hopper range.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this product range.

Basterfield B22360(NGS). Grade 304 stainless steel neutral slop hopper with a hinged bucket grid and supporting stand. Supplied without an integral flushing system.

02 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B22360(NGS)	Grade 304 Stainless Steel Neutral Slop Hopper with a Hinged Bucket Grid and Supporting Stand. Supplied Without an Integral Flushing System.	Standard configuration

03 Functional features

- 01 **Grade 304 stainless steel**

Pressed and welded stainless steel with a satin finish provides a smooth surface for routine cleaning.
- 02 **Hinged bucket grid**

The rear-hinged grid supports a bucket over the hopper and lifts to provide access for cleaning.
- 03 **Supporting stand**

Stainless steel legs support the hopper from the floor.

04 Neutral hopper

Supplied without an integral flushing rim, flush inlet or flushing mechanism.


04 Application information

Intended applications	Hospital Sinks, Sluice Rooms (Dirty Utility Rooms)
Industries	Hospitals & Clinics

05 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

Product drawings and images



PRODUCT IMAGE

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.