

MODEL SPECIFICATION

B22360(TG-106-P) – Grade 304 Stainless Steel Slop Hopper with Top-Entry Flush Pipe, Hinged Bucket Grid, Walcro 106 Flush Valve and Integral Stainless Steel P-Trap for 110 mm Soil Pipes.

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Model	B22360(TG-106-P){PSS}	Published catalogue data	4 Oct 2026

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Trap Type	P-Trap	—	—
Material	Stainless Steel Grade 304	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Bucket Grid	Yes	—	—
Flushing Inlet Orientation	Top Entry	—	—

02 Model and supply data

Parent product	B22360(TG-106) – Wall-Hung Stainless Steel Slop Hopper with Grid & Flush Valve
Typical lead time	10–15 working days
Warranty	12 months

03 Specification notes

Configuration description	Grade 304 stainless steel slop hopper with top-entry flush pipe, hinged bucket grid, Walcro 106 flush valve and integral stainless steel P-trap for 110 mm soil pipes. The wall-mounted hopper uses stainless steel gallows brackets. Its hinged grid supports receptacles and lifts for cleaning access.
Short Form Specification	SPECIFICATION USE Use this description when specifying this model. Basterfield B22360(TG-106-P). Grade 304 stainless steel slop hopper with top-entry flush pipe, hinged bucket grid, Walcro 106 flush valve and integral stainless steel P-trap for 110 mm soil pipes.

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.